

TABLEAU POUR LES INTEGRATEURS DE DONNEES

Table for data integrators

RNP RWY 29												
RMK								MAG VAR 2015 12.3°E			Ref NAVAID :	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MMIM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	Nav Spec
HLDG		WW700										
	IF	WW700								220		RNP APCH
INA WW700	TF	WW701		087	099.1	7.7						RNP APCH
	TF	WW702		051	062.9	5.5						RNP APCH
	TF	IWW29		021	033.0	4.0		2400		185		RNP APCH
	IF	WW701								220		RNP APCH
INA WW701	TF	WW702		051	062.9	5.5						RNP APCH
	TF	IWW29		021	033.0	4.0		2400		185		RNP APCH
	IF	IWW29						2400		185		RNP APCH
	TF	FWW29		319	331.1	4.4		2200	2200			RNP APCH
APCH	TF	MWW29	yes	304	316.1	4.7					-3.5° / 15.0	RNP APCH
	DF	WW710					L					RNP APCH
	TF	WW700		171	183.6	12.6	L		3000	220		RNP APCH