

TAHITI FAA'A
SID RNAV RWY 22



SID RNAV RWY 22											
RMK	xxxxx						MAG VAR 2020 12.9°E			REF NAVAID :	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
VAITE 4W											
-	CF	AA502	Y	221	234,3	-	-	400	-	-	1,0
-	DF	AA503	-	-	-	-	R	-	-	205	1,0
-	TF	VAITE	-	309	322,0	27,4	-	-	-	-	1,0
IKELO 4W											
-	CF	AA502	Y	221	234,3	-	-	400	-	-	1,0
-	DF	AA505	-	-	-	-	R	-	-	205	1,0
-	TF	IKELO	-	026	039,0	37,1	-	-	-	-	1,0
ONIDO 4W											
-	CF	AA506	-	221	234,3	-	-	-	-	-	1,0
-	TF	AA508	-	158	171	12,8	-	-	-	205	1,0
-	TF	ONIDO	-	189	202,0	18,8	-	-	-	-	1,0
BEBIG 4W											
-	CF	AA506	-	221	234,3	-	-	-	-	-	1,0
-	TF	AA508	-	158	171,0	12,8	-	-	-	205	1,0
-	TF	ONIDO	-	189	202,0	18,8	-	-	-	-	1,0
-	TF	BEBIG	-	183	196,1	15,0	-	-	-	-	1,0
ARITI 4W											
-	CA	-	-	221	234,3	-	-	500	-	-	1,0
-	DF	ARITI	-	-	-	-	R	2000	-	-	1,0
MOSMA 4W											
-	CA	-	-	221	234,3	-	-	500	-	-	1,0
-	DF	BOBIX	Y	-	-	-	R	-	-	-	1,0
-	TF	MOSMA	-	304	316,9	14,8	-	2100	-	-	1,0