

TAKAROA
PRECODING RNP B RWY 25

RNP B RWY 25												
RMK	-							MAG VAR 2020 12.0°E			REF NAVAID :-	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNIM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	NAV Spec
HLDG	-	TAVOR	-	-	-	-	-	-	-	-	-	-
INA TUPRO	IF	TUPRO	-	-	-	-	-	1500	-	-	-	RNAV 1 / RNP APCH
	TF	DADAX	-	164	176.0	5.0	-	1500	-	-	-	RNAV 1 / RNP APCH
	IF	TAVOR	-	-	-	-	-	1500	-	-	-	RNAV 1 / RNP APCH
INA TAVOR	TF	KR420	-	029	041.1	6.9	-	-	-	-	-	RNAV 1 / RNP APCH
	TF	TUPRO	-	072	084.5	5.0	-	-	-	-	-	RNAV 1 / RNP APCH
	TF	DADAX	-	164	176.0	5.0	R	1500	-	-	-	RNAV 1 / RNP APCH
	IF	DADAX	-	-	-	-	-	1500	-	-	-	RNAV 1 / RNP APCH
INA DADAX	IF	DADAX	-	-	-	-	-	1500	-	-	-	RNP APCH
APCH	TF	FKR25	-	254	266.0	5.0	-	1500	1500	-	-	RNP APCH
	TF	RW25	Yes	254	266.1	4.5	-	-	-	-	-3.0	RNP APCH
	CA	-	-	254	266.1	-	-	1000	-	-	-	RNP APCH
	DF	KR420	-	-	-	-	R	-	-	-	-	RNP APCH
	TF	TUPRO	-	072	084.5	5.0	-	1500	-	-	-	RNP APCH

