

MAUPITI

PRECODING RNP RWY 08

RNP RWY 08												
RMK	-	MAG VAR 2015 12.5°E						REF NAVAD : -				
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MMN Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	NAV Spec
HDLG	-	MOXUL	-	-	-	-	-	-	-	-	-	-
HLDG	-	MEKES	-	-	-	-	-	-	-	-	-	-
INA MEKES	IF	MEKES	-	-	-	-	-	2500	-	-	-	RNAV1 / RNP APCH
	TF	TP403	-	301	313.6	6.7	-	2500	-	-	-	RNAV1 / RNP APCH
	TF	MULER	-	258	270.9	5.7	-	1700	-	-	-	RNAV1 / RNP APCH
	TF	MOXUL	-	166	178.6	5.0	L	1700	-	-	-	RNAV1 / RNP APCH
INA MULER	IF	MULER	-	-	-	-	-	1700	-	-	-	RNAV1 / RNP APCH
	TF	MOXUL	-	166	178.6	5.0	-	1700	-	-	-	RNAV1 / RNP APCH
INA MOXUL	IF	MOXUL	-	-	-	-	-	1700	-	-	-	RNAV1 / RNP APCH
	IF	MOXUL	-	-	-	-	-	1700	-	-	-	RNP APCH
APCH	TF	TP401	-	076	088.6	5.0	-	1700	1700	-	-	RNP APCH
	TF	RW08	Yes	076	088.6	5.1	-	-	-	-	- 3.0 / 15	RNP APCH
	CA	-	-	076	088.6	-	-	1000	-	-	-	RNP APCH
	DF	TP403	-	-	-	-	L	-	-	-	-	RNP APCH
	TF	MULER	-	258	270.9	5.7	-	1700	-	-	-	RNP APCH

