

RNP RWY31												
RMK								MAG VAR 2020 0.5°E			REF NAVAID : -	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	TEPTI	-	-	-	-	-	-	-	-	-	-
	-	ATWIX	-	-	-	-	-	-	-	-	-	-
	-	PU	-	-	-	-	-	-	-	-	-	-
INA TEPTI (via BAGRO)	IF	TEPTI	-	-	-	-	-	FL070	FL100	-	-	-
	TF	LALTA	-	215	215.6	16.6	-	FL070	FL100	220	-	1.0
	TF	SUDAD	-	261	262.0	8.4	-	FL070	FL090	-	-	1.0
	TF	BAGRO	-	306	306.1	4.7	-	5000	-	-	-	1.0
	TF	IBP31	-	306	306.1	6.0	-	3000	3000	210	-	1.0
INA TEPTI (via OSVEG)	IF	TEPTI	-	-	-	-	-	FL070	FL100	-	-	-
	TF	OSVEG	-	254	254.5	23.1	-	-	5000	190	-	1.0
	TF	IBP31	-	243	243.0	4.9	-	3000	3000	-	-	1.0
INA BAGRO	IF	BAGRO	-	-	-	-	-	5000	-	-	-	-
	TF	IBP31	-	306	306.1	6.0	-	3000	3000	210	-	1.0
INA OSVEG	IF	OSVEG	-	-	-	-	-	-	5000	190	-	-
	TF	IBP31	-	243	243.0	4.9	-	3000	3000	-	-	1.0
APCH	IF	IBP31	-	-	-	-	-	3000	3000	190	-	-
	TF	FBP31	-	305	305.9	3.5	-	3000	3000	-	-	1.0
	TF	RW31	Yes	305	305.9	7.3	-	-	-	-	-3.00°/ 52	0,3
	TF	BP410	Yes	305	305.8	2.2	-	-	2000	185	-	1.0
	DF	BP412	-	-	-	-	R	-	3000	185	-	1.0
	TF	BP414		083	083.2	4.5	-	-	4000	190	-	1.0
	TF	BP416		141	141.6	8.5	-	-	-	-	-	1.0
	TF	OSVEG		186	186.0	4.5	-	-	-	-	-	1.0
	TF	IBP31		243	243.0	4.9	-	3000 (1)	4000	190	-	1.0
	TF	PU	Yes	306	306.2	5,3	-	3000	4000	190	-	1.0
	HM	PU	-	-	-	-	-	-	-	-	-	-

(1) 3000 ft obligatoire si nouvelle approche en fin d'API / 3000 ft mandatory if new approach at the end of missed approach