

AJACCIO NAPOLEON BONAPARTE
STAR RNAV CONFIGURATION PARATA
(Protégées pour / Protected for CAT A, B, C, D)

STAR RNAV RWY 20 PARATA											
RMK	GNSS only						MAG VAR 2020 2.7°E			REF NAV AID : -	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
HLDG											
IDDOL	-	-	-	-	-	-	-	-	-	-	-
LONSU 3N											
-	IF	LONSU	-	-	-	-	-	-	-	-	-
-	TF	BEBEV	-	148	150.7	38.4	-	-	-	-	1.0
-	TF	LASVA	-	166	168.7	14.6	-	-	-	-	1.0
-	TF	IDDOL	-	133	135.8	6.6	-	4000	FL100	220	1.0
TORTU 3N											
-	IF	TORTU	-	-	-	-	-	-	-	-	-
-	TF	BEBEV	-	195	198.0	73.8	-	-	-	-	1.0
-	TF	LASVA	-	166	168.7	14.6	-	-	-	-	1.0
-	TF	IDDOL	-	133	135.8	6.6	-	4000	FL100	220	1.0
BTA 3N											
-	IF	BTA	-	-	-	-	-	-	-	-	-
-	TF	KJ850	-	243	245.3	33.5	-	FL125	-	-	1.0
-	TF	KJ830	-	242	244.8	8.0	-	FL085	-	-	1.0
-	TF	BEBEV	-	242	244.7	9.0	-	-	-	-	1.0
-	TF	LASVA	-	166	168.7	14.6	-	-	-	-	1.0
-	TF	IDDOL	-	133	135.8	6.6	-	4000	FL100	220	1.0
VAREK 3N											
-	IF	VAREK	-	-	-	-	-	-	-	-	-
-	TF	LASVA	-	128	130.2	31.0	-	-	-	-	1.0
-	TF	IDDOL	-	133	135.8	6.6	-	4000	FL100	220	1.0
RUBAS 3N											
-	IF	RUBAS	-	-	-	-	-	-	-	-	-
-	TF	LOKDU	-	107	109.5	69.5	-	-	-	-	1.0
-	TF	LASVA	-	88	090.3	021.3	-	-	-	-	1.0
-	TF	IDDOL	-	133	135.8	6.6	-	4000	FL100	220	1.0
NEGAT 3N											
-	IF	NEGAT	-	-	-	-	-	-	-	-	-
-	TF	SIRSA	-	063	066.0	30.5	-	-	-	-	1.0
-	TF	KJ800	-	350	352.6	20.0	-	-	FL100	220	1.0
-	TF	LASVA	-	062	065.0	4.2	-	-	-	-	1.0
-	TF	IDDOL	-	133	135.8	6.6	-	4000	-	-	1.0
POULP 3N											
-	IF	POULP	-	-	-	-	-	-	FL 140	-	-
-	TF	SIRSA	-	344	347.0	17.5	-	-	-	-	1.0
-	TF	KJ800	-	350	352.6	20.0	-	-	FL100	220	1.0
-	TF	LASVA	-	062	065.0	4.2	-	-	-	-	1.0
-	TF	IDDOL	-	133	135.8	6.6	-	4000	-	-	1.0
TEREZ 3N											
-	IF	TEREZ	-	-	-	-	-	-	FL 140	-	-
-	TF	KJ505	-	341	343.2	36.5	-	-	-	-	1.0
-	TF	KJ506	-	311	314.0	8.8	-	-	FL 100	-	1.0
-	TF	KJ810	-	282	284.9	3.5	-	-	-	220	1.0
-	TF	LASVA	-	224	226.2	4.7	-	-	-	-	1.0
-	TF	IDDOL	-	133	135.8	6.6	L	4000	-	-	1.0
ASKAG 3N											
-	IF	ASKAG	-	-	-	-	-	-	FL 140	-	-
-	TF	KJ 870	-	283	285.9	41.5	-	FL100	-	-	1.0
-	TF	KJ 506	-	283	285.3	9.2	-	-	FL 100	-	1.0
-	TF	KJ810	-	282	284.9	3.5	-	-	-	220	1.0
-	TF	LASVA	-	224	226.2	4.7	-	-	-	-	1.0
-	TF	IDDOL	-	133	135.8	6.6	L	4000	-	-	1.0
VAREK 3F											
-	IF	VAREK	-	-	-	-	-	-	-	-	-
-	TF	KJ601	-	109	111.9	25.0	-	-	6000	-	1.0