

PRECODING RNP RWY 16

RNP RWY 16												
RMK	GNSS seulement / only							MAG VAR 2020 1.8°E			REF NAVAID : -	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	Navigation Accuracy (NM)
HLDG	-	ARBON	-	-	-	-	-	-	-	-	-	-
	-	RIPTU	-	-	-	-	-	-	-	-	-	-
	-	GOMET	-	-	-	-	-	-	-	-	-	-
	-	TALAR	-	-	-	-	-	-	-	-	-	-
INA GOMET 1T	IF	GOMET	-	-	-	-	-	-	-	-	-	-
	TF	LY619	-	327	328.4	10.3	-	-	-	-	-	1.0
	TF	LY609	-	356	357.6	8.6	-	FL 100	-	-	-	1.0
	TF	LY607	-	356	357.6	6.8	-	FL 070	-	-	-	1.0
	TF	LY605	-	331	332.3	4.9	-	-	-	-	-	1.0
	TF	LY603	-	316	317.9	8.0	-	5000	-	-	-	1.0
	TF	LY601	-	308	309.8	5.6	-	-	-	-	-	1.0
INA RIPTU 1T	TF	FAGOR	-	237	239.3	9.5	-	3000	-	220	-	1.0
	IF	RIPTU	-	-	-	-	-	FL 70	-	-	-	-
	TF	LY601	-	237	239.1	13.1	-	-	-	-	-	1.0
INA ARBON 1T	TF	FAGOR	-	237	239.3	9.5	-	3000	-	220	-	1.0
	IF	ARBON	-	-	-	-	-	FL 100	-	-	-	-
	TF	LY602	-	012	013.8	16.5	-	FL 080	-	-	-	1.0
	TF	LY600	-	331	332.6	23.5	-	5000	-	220	-	1.0
INA TALAR 1T	TF	FAGOR	-	079	081.1	5.9	R	3000	-	220	-	1.0
	IF	TALAR	-	-	-	-	-	FL 70	-	-	-	-
	TF	LY600	-	123	124.7	6.1	-	5000	-	-	-	1.0
APCH	TF	FAGOR	-	079	081.1	5.9	-	3000	-	220	-	1.0
	IF	FAGOR	-	-	-	-	-	3000	-	220	-	-
	TF	FLY16	-	162	163.4	4.1	-	3000	3000	-	-	1.0
	TF	RW16	Yes	162	163.4	7.2	-	-	-	-	-3.0 / 15	0.3
	TF	LY620	-	162	163.4	7.3	-	-	-	-	-	1.0
TF	ARBON	-	190	192.1	20.4	-	5000	-	-	-	1.0	