

VILLACOUBLAY VELIZY
STAR RNAV RWY27
(Protégées pour / Protected for CAT A, B, C, D)

RMK	GNSS - DME / DME							MAG VAR 2020 1°E			REF NAV AID :-	
Procedure Identification	Path Terminator	Waypoint Identification	DTG THRXX (NM)	Fly Over	Direction MAG (*)	Direction True (*)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	NAV Spec
HOLDING												
LORNI	HM	LORNI		Yes	255	255,5	T 1 min	R	FL070	FL140	230	RNAV 1
	HM	LORNI		Yes	255	255,5	T 1 min 30	R	FL150	FL170	240	RNAV 1
MOLBA	HM	MOLBA		Yes	313	314,2	T 1 min	R	FL070	FL140	230	RNAV 1
ODILO	HM	ODILO		Yes	033	034,1	WD 9,7	R	FL070	FL140	230	RNAV 1
XERAM	HM	XERAM		Yes	253	253,7	T 1 min 30	L	FL200	FL280	265	RNAV 1
OKRIX	HM	OKRIX		Yes	337	337,9	T 1 min	L	FL070	FL140	230	RNAV 1
	HM	OKRIX		Yes	337	337,9	T 1 min 30	L	FL150	FL240	265	RNAV 1
AMB	HM	AMB		Yes	011	012,3	T 1 min 30	R	FL200	FL280	265	RNAV 1
CAD	HM	CAD		Yes	018	018,9	T 1 min	R	FL070	FL140	230	RNAV 1
	HM	CAD		Yes	018	018,9	T 1 min 30	R	FL150	FL240	265	RNAV 1