

**NUKU HIVA**  
**PRECODING RNP RWY 24**

RNP RWY 24												
RMK	MAG VAR 2020 10.8°E						REF NAVAID :					
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MINM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	NAV Spec
HLDG	-	NITOR	-	-	-	-	-	-	-	-	-	-
HLDG	-	MD406	-	-	-	-	-	-	-	-	-	-
INA NITOR	IF	NITOR	-	-	-	-	-	5800	-	-	-	RNAV 1 / RNP APCH
	TF	NISAK	-	305	316.0	14.0	-	2500	-	-	-	RNAV 1 / RNP APCH
INA MD406	IF	MD406	-	-	-	-	-	2500	-	-	-	RNAV 1 / RNP APCH
	TF	NISAK	-	148	158.2	5.0	-	2500	-	-	-	RNAV 1 / RNP APCH
	IF	NISAK	-	-	-	-	-	2500	-	-	-	RNP APCH
	TF	FMD24	-	238	248.2	5.0	-	2500	2500	-	-	RNP APCH
	TF	RW24	Yes	238	248.2	7.1	-	-	-	-	-3.0 / 15	RNP APCH
APCH	CA	-	-	238	248.2	-	R	1500	-	-	-	RNP APCH
	DF	MD404	-	-	-	-	-	-	-	-	-	RNP APCH
	TF	MD406	-	056	067.0	7.4	-	2500	-	-	-	RNP APCH

↑ ↑ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↑ ↑ ↑ ↑ ↓ ↓ ↓