

RNP RWY28												
RMK	-							MAG VAR 2025 1.1°E			REF NAVAID :-	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNIM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	CY286	-	-	-	-	-	-	-	-	-	-
	IF	CY286	yes	-	-	-	-	-	-	-	-	-
	DF	CY284	-	-	-	-	L	-	-	-	-	1.0
	TF	CY282	-	094	095.4	3.4	-	2000	2500	-	-	1.0
	TF	ICY28	-	010	011.4	4.0	-	2000	2000	-	-	1.0
INA CY282	IF	CY282	-	-	-	-	-	2000	2500	-	-	-
	TF	ICY28	-	010	011.4	4.0	-	2000	2000	-	-	1.0
INA CY281	IF	CY281	-	-	-	-	-	2000	2500	-	-	-
	TF	ICY28	-	190	191.5	4.0	-	2000	2000	-	-	1.0
INA ICY28	IF	ICY28	-	-	-	-	-	2000	2000	-	-	-
	IF	ICY28	-	-	-	-	-	2000	2000	-	-	-
APCH	TF	FCY28	-	280	281.4	3.5	-	2000	2000	-	-	1.0
	TF	RW28	yes	280	281.4	5.9	-	-	-	-	- 3.00 / 50	0.3
	DF	CY286	yes	-	-	-	R	2000	2000	-	-	1.0