

INA RNAV (GNSS) RWY 32L												
RMK	GNSS only - Linked to FNA RNP RWY 32L et/and FNA ILS Z ou/ or LOC Z RWY 32L Procedure developed under CDO concept											
	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	Navigation Accuracy (NM)
	HLDG	-	ADIMO	-	-	-	-	-	-	-	-	-
	HLDG	-	FUZAP	-	-	-	-	-	-	-	-	-
	HLDG	-	SULIT	-	-	-	-	-	-	-	-	-
INA ADIMO	IF	ADIMO	-	-	-	-	-	FL080	-	-	-	-
	TF	BO606	-	266	267.5	7.9	-	-	230	-	-	1.0
	TF	BO603	-	266	267.4	5.0	-	4000	-	-	-	1.0
	TF	IO32L	-	256	257.5	3.8	-	3000	-	210	-	1.0
INA AGENO	IF	AGENO	-	-	-	-	-	FL080	-	-	-	-
	TF	BO602	-	121	123.0	10.4	L	5000	-	-	-	1.0
	TF	IO32L	-	027	028.3	5.0	-	3000	-	210	-	1.0
	IF	FUZAP	-	-	-	-	-	FL080	-	-	-	-
INA FUZAP	TF	BO608	-	188	189.8	9.4	-	-	-	-	-	1.0
	TF	BO607	-	140	142.0	7.7	-	FL080	-	-	-	1.0
	TF	BO605	-	140	142.0	8.1	-	5000	-	-	-	1.0
	TF	BO604	-	185	186.9	4.0	-	-	230	-	-	1.0
	TF	BO603	-	185	186.9	4.3	-	4000	-	-	-	1.0
	TF	IO32L	-	256	257.5	3.8	-	3000	-	210	-	1.0
	IF	OGRIL	-	-	-	-	-	FL080	-	-	-	-
	TF	BO602	-	058	059.4	12.1	-	5000	-	-	-	1.0
INA OGRIL	TF	IO32L	-	027	028.3	5.0	-	3000	-	210	-	1.0
INA SULIT	IF	SULIT	-	-	-	-	-	FL080	-	-	-	-
	TF	BO602	-	084	085.9	9.7	-	5000	-	-	-	1.0
	TF	IO32L	-	027	028.3	5.0	-	3000	-	210	-	1.0