

MELUN VILLAROCHE

SID RNAV RWY 10

(Protégés pour / Protected for CAT A, B, C)

SID RNAV RWY 10											
RMK	GNSS or DME/DME/IRU						MAG VAR 2020 1,1°E			REF NAVAID : MLN	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
ARSIL 5E											
-	CA	-	-	102	103.5	-	-	700	-	-	1.0
-	DF	ADDOZ	-	-	-	-	-	2000	2000	-	1.0
-	TF	PM506	-	079	080.0	6.6	-	-	3000	-	1.0
-	TF	PM507	-	079	080.1	6.3	-	-	4000	-	1.0
-	TF	APPOC	-	079	080.2	8.0	-	-	-	-	1.0
-	TF	ARSIL	-	081	082.5	29.5	-	-	5000	-	1.0
LUREN 5E											
-	CA	-	-	102	103.5	-	-	700	-	-	1.0
-	DF	ADDOZ	-	-	-	-	-	2000	2000	-	1.0
-	TF	PM510	-	118	118.9	3.5	-	3000	3000	-	1.0
-	TF	PM511	-	118	119.0	5.3	-	4000	4000	-	1.0
-	TF	PM516	-	118	119.1	24.2	-	-	5000	-	1.0
-	TF	LUREN	-	118	119.4	17.7	-	-	FL 080	-	1.0
OLZOM 5E											
-	CA	-	-	102	103.5	-	-	700	-	-	1.0
-	DF	ADDOZ	-	-	-	-	-	2000	2000	-	1.0
-	TF	PM512	-	182	183.5	7.8	-	3000	3000	-	1.0
-	TF	DORDI	-	182	183.4	5.4	-	-	5000	-	1.0
-	TF	OLZOM	-	259	259.8	21.5	-	-	FL 080	-	1.0
POLLY 5E											
-	CA	-	-	102	103.5	-	-	700	-	-	1.0
-	DF	ADDOZ	-	-	-	-	-	2000	2000	-	1.0
-	TF	PM512	-	182	183.5	7.8	-	3000	3000	-	1.0
-	TF	DORDI	-	182	183.4	5.4	-	-	5000	-	1.0
-	TF	POLLY	-	182	183.5	19.6	-	-	FL 080	-	1.0
TRO 5E											
-	CA	-	-	102	103.5	-	-	700	-	-	1.0
-	DF	ADDOZ	-	-	-	-	-	2000	2000	-	1.0
-	TF	PM508	-	101	102.5	4.2	-	-	3000	-	1.0
-	TF	PM509	-	101	102.6	5.5	-	-	4000	-	1.0
-	TF	ATTUC	-	102	102.7	9.6	-	-	5000	-	1.0
-	TF	PM514	-	103	104.3	18.8	-	-	5000	-	1.0
-	TF	TRO	-	103	104.6	9.5	-	-	FL 080	-	1.0