

PONTOISE CORMEILLES EN VEXIN

STAR RNAV RWY ALL

Réacteurs et Hélices / Turboprops and Turboprops

(Protégés pour / Protected for CAT A, B, C, D)

STAR RNAV RWY ALL											
RMK	MAG VAR 2025 1.7 °E Ref NAVAID :										
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigatoin Accuracy (NM)
MATIX 1T (FIR)											
-	IF	MATIX	-	-	-	-	-	-	-	280	-
-	TF	VAKOS	-	172	173.8	31.9	-	-	-	-	1.0
-	TF	IPNOB	-	274	275.2	17.7	R	-	-	-	1.0
-	TF	OBOBI	-	230	232.1	23.4	-	-	-	-	1.0
-	TF	ICQAR	-	250	251.6	22.5	-	-	-	-	1.0
-	TF	OZHIS	-	266	268.1	11.0	-	-	-	-	1.0
MOPIL 1T (UIR)											
-	IF	MOPIL	-	-	-	-	-	-	FL260	280	-
-	TF	XERAM	-	181	182.7	33.1	-	-	-	-	1.0
-	TF	IPNOB	-	268	270.0	20.1	-	-	-	-	1.0
-	TF	OBOBI	-	230	232.1	23.4	-	-	-	-	1.0
-	TF	ICQAR	-	250	251.6	22.5	-	-	-	-	1.0
-	TF	OZHIS	-	266	268.1	11.0	-	-	-	-	1.0
VEDUS 1T (UIR FIR FL > 105)											
-	IF	VEDUS	-	-	-	-	-	-	FL260	280	RNAV 1
-	TF	XERAM	-	269	270.5	27.9	-	-	-	-	RNAV 1
-	TF	IPNOB	-	268	270.0	20.1	-	-	-	-	RNAV 1
-	TF	OBOBI	-	230	232.1	23.4	-	-	-	-	RNAV 1
-	TF	ICQAR	-	250	251.6	22.5	-	-	-	-	RNAV 1
-	TF	OZHIS	-	266	268.1	11.0	-	-	-	-	RNAV 1
SONUR 1T (FIR FL > 105)											
-	IF	SONUR	-	-	-	-	-	-	-	280	RNAV 1
-	TF	GIMER	-	252	254.2	15.6	-	-	-	-	RNAV 1
-	TF	ENORI	-	310	310.6	10.1	-	-	-	-	RNAV 1
-	TF	IPNOB	-	309	309.4	11.4	-	-	-	-	RNAV 1
-	TF	OBOBI	-	230	232.1	23.4	-	-	-	-	RNAV 1
-	TF	ICQAR	-	250	251.6	22.5	-	-	-	-	RNAV 1
-	TF	OZHIS	-	266	268.1	11.0	-	-	-	-	RNAV 1