

IAF : OKIPA

TF : Track to Fix

COULOMMIERS
CLM 112.9
Ch 76 X

OKIPA
IAF
Réacteurs/Jets FL 110
FL 070
Hélices/Propellers FL 100
FL 070

URELO
TF 302°
302° 8.0
122°
122°

NANOP
TF 308°
8.1
TF 318°
318° 10.2
138°
138°

ERTIP
TF 319°
319° 11.7
25.3

AVLON
TF 007°
007° 51.8
MOU 9W-9P
PIBAT 9W-9P
48.8

PIBAT
TF 337°
337° 48.8

DIJON
DJL 111.45
Ch 51 Y

FF 301
Réacteurs/Jets FL 160
Hélices/Propellers FL 150
MAX IAS 250 kt

FF 302
MAX IAS 280 kt
FL 280

FF 304
Hélices/Propellers FL 280

EPINAL
EPL 113.0
TF 267°
267° 73.0
EPL 9W-9P

ROLAMPONT
RLP Ch 120 X
(117.3)
TF 291°
291° 36.6
RLP 9W-9P

TINIL
TF 319°
319° 11.7
25.3

MOULINS
MOU 116.7
Ch 114 X

ALT / HGT : ft
Distances : NM

0 10 NM

HLDG OKIPA	
HAUTE / HIGH 48°36' 40.7" N 003° 33' 48.6" E	BASSE / LOW
FL 150/190 RAP 302° Gauche/Left 1 min 30 IAS 240 kt	FL 070/140 RAP 302° Gauche/Left 1 min IAS 230 kt

HLDG NANOP	
HAUTE / HIGH 48°15' 43" N 004° 14' 22" E	BASSE / LOW
FL 150/280 RAP 318° Gauche/Left 1 min 30 IAS 265 kt	FL 070/140 RAP 318° Gauche/Left 1 min IAS 230 kt

See instructions STAR LFPG AD 2.22.
RADIOCOMMUNICATION FAILURE :
 See special instructions STAR described on LFPG AD 2.22.