

ILS RWY 27												
RMK	MAG VAR 2025 1.4°E						REF NAVAID :-					
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
INA BE271	IF	BE271	-	-	-	-	-	2500	4400	185	-	-
	TF	IBE27	-	183	184.5	5.1	-	2500	2500	185	-	1.0
INA BE272	IF	BE272	-	-	-	-	-	2500	4000	185	-	-
	TF	IBE27	-	003	004.5	5.1	-	2500	2500	185	-	1.0
	IF	BE090	Yes	-	-	-	-	2500	5000	210	-	-
INA BE090	DF	BE276	-	-	-	-	-	2500	4000	185	-	1.0
	TF	BE272	-	093	094.5	5.0	-	2500	4000	185	-	1.0
	TF	IBE27	-	003	004.5	5.1	-	2500	2500	185	-	1.0
	IF	IBE27	-	-	-	-	-	2500	2500	185	-	-
See chart ILS RWY 27												
APCH	-	BE280	Yes	-	-	-	-	-	2500	180	-	1.0
	DF	BE274	-	-	-	-	L	-	2500	185	-	1.0
	TF	BE272	-	093	094.3	12.7	-	2500	2500	185	-	1.0