

RNP RWY 09												
RMK	MAG VAR 2025 0.9°E										REF NAV AID :-	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	RL	-	-	-	-	-	-	-	-	-	-
INA BH092	IF	BH092	-	-	-	-	-	-	5000	200	-	-
	TF	BH094	-	201	201.9	6.3	-	-	3000	200	-	1.0
	TF	IBH09	-	123	124.0	3.2	-	2000	2500	185	-	1.0
INA BH091	IF	BH091	-	-	-	-	-	-	5000	200	-	-
	TF	BH093	-	324	324.6	7.5	-	-	3000	200	-	1.0
	TF	IBH09	-	060	060.9	3.2	-	2000	2500	185	-	1.0
INA RL	IF	RL	Yes	-	-	-	-	-	5000	200	-	-
	DF	BH091	-	-	-	-	-	-	5000	200	-	1.0
	TF	BH093	-	324	324.6	7.5	-	-	3000	200	-	1.0
	TF	IBH09	-	060	060.9	3.2	-	2000	2500	185	-	1.0
APCH	IF	IBH09	-	-	-	-	-	2000	2500	185	-	-
	TF	FBH09	-	092	092.3	3.2	-	2000	2000	-	-	1.0
	TF	RW09	Yes	092	092.3	5.1	-	-	-	-	-3.50 / 49	0.3
	TF	RL	Yes	092	092.4	4.5	-	-	4000	200	-	1.0
	DF	BH091	-	-	-	-	R	-	5000	200	-	1.0