

RNP RWY 27												
RMK	MAG VAR 2025 0.9°E						REF NAVAIID :-					
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	RL	-	-	-	-	-	-	-	-	-	-
INA XERGI	IF	XERGI	-	-	-	-	-	2500	2500	200	-	-
	TF	IBH27	-	182	182.8	6.1	-	2500	2500	185	-	1.0
INA BEMAX	IF	BEMAX	-	-	-	-	-	3000	3000	-	-	-
	TF	IBH27	-	272	272.8	6.0	-	2500	2500	185	-	1.0
INA DEGAX	IF	DEGAX	-	-	-	-	-	2500	2500	200	-	-
	TF	IBH27	-	002	002.8	6.3	-	2500	2500	185	-	1.0
	IF	RL	Yes	-	-	-	-	2500	FL090	220	-	-
INA RL	TF	BH501	-	124	125.1	6.5	-	2500	2500	200	-	1.0
	TF	BH505	-	092	092.5	2.7	-	2500	2500	200	-	1.0
	TF	IBH27	-	002	002.8	3.5	L	2500	2500	185	-	1.0
	IF	IBH27	-	-	-	-	-	2500	2500	185	-	-
	TF	FBH27	-	272	272.6	4.9	-	2500	2500	-	-	1.0
APCH	TF	RW27	Yes	272	272.5	7.0	-	-	-	-	-3.20 / 45	0.3
	TF	BH512	Yes	272	272.4	8.6	-	-	2500	220	-	1.0
	TF	BH514	Yes	341	342.3	9.6	-	4000	-	220	-	1.0
	DF	RL	-	-	-	-	R	2500	FL090	220	-	1.0