

RNP RWY 03												
RMK	MAG VAR 2025 1.3°E											REF NAVAI : -
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	BI030	-	-	-	-	-	-	-	-	-	-
	-	BI032	-	-	-	-	-	-	-	-	-	-
INA BI032	IF	BI032	-	-	-	-	-	3000	4000	200	-	-
	TF	BI034	-	179	179.9	8.0	-	3000	3000	185	-	1.0
	TF	BI030	-	119	120.4	4.0	-	3000	3000	185	-	1.0
INA BI034	IF	BI034	-	-	-	-	-	3000	3000	185	-	-
	TF	BI030	-	119	120.4	4.0	-	3000	3000	185	-	1.0
	IF	BI030	-	-	-	-	-	3000	FL060	220	-	-
INA BI030	TF	BI031	-	154	155.4	9.3	-	-	4500	200	-	1.0
	TF	BI033	-	223	224.4	15.3	-	3000	3000	185	-	1.0
	TF	BI030	-	299	300.5	4.0	-	3000	3000	185	-	1.0
	IF	BI033	-	-	-	-	-	3000	3000	185	-	-
INA BI033	TF	BI030	-	299	300.5	4.0	-	3000	3000	185	-	1.0
	IF	BI030	-	-	-	-	-	3000	3000	185	-	-
APCH	TF	FBI03	-	029	030.5	3.5	-	3000	3000	-	-	1.0
	TF	RW03	Yes	029	030.5	8.0	-	-	-	-	-3.00 / 49	0.3
	TF	BI030	Yes	029	030.6	8.7	-	-	2000	200	-	1.0
	DF	BI031	-	-	-	-	R	-	4500	200	-	1.0
	TF	BI033	-	223	224.4	15.3	-	3000	3000	185	-	1.0