

POITIERS BIARD
SID RNAV RWY 21
(Codage proposé / Proposed coding)

SID RNAV RWY 21											
RMK	GNSS only						MAG VAR 2025 1.3°E			REF NAVAID : POI	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
VERAC 6V											
-	CF	BI520	-	209	210.6	-	-	-	3500	230	1.0
-	TF	VERAC	-	202	203.7	15.5	-	7000	-	-	1.0
ABSIE 6V											
-	CF	BI520	-	209	210.6	-	-	-	3500	230	1.0
-	TF	BI524	-	276	276.9	7.0	-	-	-	250	1.0
-	TF	ABSIE	-	275	276.8	22.7	-	-	-	-	1.0
GINON 6V											
-	CF	BI520	-	209	210.6	-	-	-	3500	230	1.0
-	TF	BI524	-	276	276.9	7.0	-	-	-	250	1.0
-	TF	BI214	-	005	006.1	6.4	-	-	-	-	1.0
-	TF	GINON	-	004	005.8	31.4	-	-	-	-	1.0
OMARI 6V											
-	CF	BI520	-	209	210.6	-	-	-	3500	230	1.0
-	TF	BI524	-	276	276.9	7.0	-	-	-	250	1.0
-	TF	BI214	-	005	006.1	6.4	-	-	-	250	1.0
-	TF	OMARI	-	042	043.3	43.1	-	-	-	-	1.0
OLINO 6V											
-	CF	BI520	Yes	209	210.6	-	-	-	3500	230	1.0
-	DF	BI521	-	-	-	-	L	-	-	250	1.0
-	TF	OLINO	-	043	044.1	30.1	-	-	-	-	1.0
BALAN 6V											
-	CF	BI520	Yes	209	210.6	-	-	-	3500	230	1.0
-	DF	BI521	-	-	-	-	L	-	-	250	1.0
-	TF	BALAN	-	090	091.0	20.5	-	-	-	-	1.0