

FNA RNP RWY 14L

| RMK | MAG VAR 2025 1.7°E | | | | | | | | | | REF NAVAID : | | |
|------|--------------------|-----------------|-------------------------|----------|-------------------|--------------------|---------------|----------------|-------------------------------|------------------------------|--------------|-------------------------------|--------------------------|
| | Leg sequence | Path Terminator | Waypoint Identification | Fly Over | Direction MAG (°) | Direction True (°) | Distance (NM) | Turn direction | MINM Altitude (FL or AMSL ft) | MAX Altitude (FL or AMSL ft) | MAX IAS (kt) | Vertical angle (°) / TCH (ft) | Navigation Accuracy (NM) |
| | - | | | | | | | | | | | | |
| HLDG | - | | FUZAP | - | - | - | - | - | - | - | - | - | - |
| | | IF | IO14L | - | - | - | - | 3000 | - | 210 | - | - | - |
| | | TF | FO14L | - | 141 | 142.8 | 3.6 | 3000 | 3000 | - | - | - | 1.0 |
| | | TF | RW14L | Yes | 141 | 142.8 | 7.7 | - | - | - | -3.00 / 50 | - | 0.3 |
| | | TF | BO512 | - | 143 | 144.6 | 5.7 | - | - | - | - | - | 1.0 |
| | | TF | BO513 | - | 079 | 080.9 | 4.4 | 3000 | - | 190 | - | - | 1.0 |
| | | TF | BO514 | - | 001 | 002.7 | 6.1 | - | - | - | - | - | 1.0 |
| | | TF | BO515 | - | 330 | 331.8 | 11.0 | 4000 | 4000 | - | - | - | 1.0 |
| | | TF | FUZAP | Yes | 007 | 008.6 | 8.9 | 5000 | - | - | - | - | 1.0 |