

TOULOUSE BLAGNAC
PRECODING INA RNAV (GNSS) RWY 32R

RMK	INA RNAV (GNSS) RWY 32R											REF NAV AID :	
	Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MMM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	Navigation Accuracy (NM)
	GNSS only - Linked to FNA RNP RWY 32R et/and FNA ILS Z ou/ or LOC Z RWY 32R Procedure développée under CDO concept												
	HLDG	-	ADIMO	-	-	-	-	-	-	-	-	-	-
	HLDG	-	FUZAP	-	-	-	-	-	-	-	-	-	-
	HLDG	-	SULIT	-	-	-	-	-	-	-	-	-	-
	INA ADIMO	IF	ADIMO	-	-	-	-	FL080	-	-	-	-	-
		TF	BO606	-	266	267.5	7.9	-	-	230	-	-	1.0
		TF	BO603	-	266	267.4	5.0	4000	-	-	-	-	1.0
		TF	IO32R	-	251	253.1	3.5	3000	-	210	-	-	1.0
		IF	AGENO	-	-	-	-	FL080	-	-	-	-	-
	INA AGENO	TF	BO602	-	121	123.0	10.4	5000	-	-	-	-	1.0
		TF	IO32R	-	031	032.9	5.0	3000	-	210	-	-	1.0
		IF	FUZAP	-	-	-	-	FL080	-	-	-	-	-
		TF	BO608	-	188	189.8	9.4	-	-	-	-	-	1.0
		TF	BO607	-	140	142.0	7.7	FL080	-	-	-	-	1.0
	INA FUZAP	TF	BO605	-	140	142.0	8.1	5000	-	-	-	-	1.0
		TF	BO604	-	185	186.9	4.0	-	-	230	-	-	1.0
		TF	BO603	-	185	186.9	4.3	4000	-	-	-	-	1.0
		TF	IO32R	-	251	253.1	3.5	3000	-	210	-	-	1.0
		IF	OGRIL	-	-	-	-	FL080	-	-	-	-	-
	INA OGRIL	TF	BO602	-	058	059.4	12.1	5000	-	-	-	-	1.0
		TF	IO32R	-	031	032.9	5.0	3000	-	210	-	-	1.0
		IF	SULIT	-	-	-	-	FL080	-	-	-	-	-
	INA SULIT	TF	BO602	-	084	085.9	9.7	5000	-	-	-	-	1.0
		TF	IO32R	-	031	032.9	5.0	3000	-	210	-	-	1.0