

| RNP Y RWY 27 (LNAV-VNAV seulement / only)          |    |                    |                         |          |                   |                    |               |                |                              |                              |              |                               |                          |
|--|----|--------------------|-------------------------|----------|-------------------|--------------------|---------------|----------------|------------------------------|------------------------------|--------------|-------------------------------|--------------------------|
| RMK  | -  | MAG VAR 2025 1.0°E |                         |          |                   |                    |               |                |                              |                              |              | REF NAV AID : BMC             |                          |
|  |    | Path Terminator    | Waypoint Identification | Fly Over | Direction MAG (°) | Direction True (°) | Distance (NM) | Turn direction | MNM Altitude (FL or AMSL ft) | MAX Altitude (FL or AMSL ft) | MAX IAS (kt) | Vertical angle (°) / TCH (ft) | Navigation Accuracy (NM) |
| INA BS272  | IF | BS272              | -                       | -        | -                 | -                  | -             | 2000           | -                            | 140                          | -            | -                             | -                        |
|  | TF | IBS27              | -                       | 360      | 001.1             | 5.0                | -             | 2000           | 2000                         | 140                          | -            | 1.0                           | -                        |
| INA LAPOS  | IF | LAPOS              | -                       | -        | -                 | -                  | -             | -              | -                            | 140                          | -            | -                             | -                        |
|  | TF | IBS27              | -                       | 294      | 295.5             | 3.6                | -             | 2000           | 2000                         | 140                          | -            | 1.0                           | -                        |
| INA BS271 sur instruction CTL / on ATC instruction | IF | BS271              | -                       | -        | -                 | -                  | -             | 2000           | -                            | 140                          | -            | -                             | -                        |
|  | TF | IBS27              | -                       | 180      | 181.1             | 5.0                | -             | 2000           | 2000                         | 140                          | -            | 1.0                           | -                        |
| INA BRS  | IF | BRS                | -                       | -        | -                 | -                  | -             | -              | -                            | 140                          | -            | -                             | -                        |
|  | TF | BS274              | -                       | 132      | 133.1             | 7.2                | -             | -              | -                            | -                            | -            | 1.0                           | -                        |
|  | TF | BS272              | -                       | 090      | 091.0             | 3.0                | -             | 2000           | -                            | 140                          | -            | 1.0                           | -                        |
|  | TF | IBS27              | -                       | 360      | 001.1             | 5.0                | L             | 2000           | 2000                         | 140                          | -            | 1.0                           | -                        |
| APCH   | IF | IBS27              | -                       | -        | -                 | -                  | -             | 2000           | 2000                         | 140                          | -            | -                             | -                        |
|  | TF | FBS27              | -                       | 270      | 271.1             | 3.0                | -             | 2000           | 2000                         | 120                          | -            | 1.0                           | -                        |
|  | TF | RW27               | Yes                     | 270      | 271.1             | 5.3                | -             | -              | -                            | 110                          | -3.3°/ 39    | 0.3                           | -                        |
|  | DF | BS270              | -                       | -        | -                 | -                  | L             | -              | -                            | 140                          | -            | 1.0                           | -                        |
|  | TF | BS272              | -                       | 090      | 091.0             | 8.0                | L             | 2000           | -                            | 140                          | -            | 1.0                           | -                        |