

RNP Z RWY 27 (LPV seulement /only)													
RMK	-	MAG VAR 2025 1.0° E										REF NAV AID : BMC	
		Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MMM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
Leg sequence													
INA BS272	IF	BS272	-	-	-	-	-	2000	-	140	-	-	-
	TF	IBS27	-	360	001.1	5.0	-	2000	2000	140	-	1.0	
INA LAPOS	IF	LAPOS	-	-	-	-	-	-	-	140	-	-	-
	TF	IBS27	-	294	295.5	3.6	-	2000	2000	140	-	1.0	
INA BS271 sur instruction CTL/ on ATC instruction	IF	BS271	-	-	-	-	-	2000	-	140	-	-	-
	TF	IBS27	-	180	181.1	5.0	-	2000	2000	140	-	1.0	
INA BRS	IF	BRS	-	-	-	-	-	-	-	140	-	-	-
	TF	BS274	-	132	133.1	7.2	-	-	-	-	-	1.0	
	TF	BS272	-	090	091.0	3.0	-	2000	-	140	-	1.0	
	TF	IBS27	-	360	001.1	5.0	L	2000	2000	140	-	1.0	
	IF	IBS27	-	-	-	-	-	2000	2000	140	-	-	-
	TF	FBS27	-	270	271.1	3.0	-	2000	2000	120	-	1.0	
APCH	TF	BS27Z	Yes	270	271.1	5.3	-	-	-	110	-3.3°/39	0.3	
	DF	BS270	-	-	-	-	L	-	-	140	-	1.0	
	TF	BS272	-	090	091.0	8.0	L	2000	-	140	-	1.0	