

RNP RWY 09												
RMK	MAG VAR 2025 0.9°E											REF NAV AID :-
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MINM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	OSGOT	Yes	161	161.6	3.3	R	3000	FL070	200	-	-
INA OSGOT	IF	OSGOT	-	-	-	-	-	3000	5000	-	-	-
	TF	BZ092	-	233	233.7	8.5	-	2000	3500	200	-	1.0
	TF	IBZ09	-	178	179.0	4.5	-	2000	2500	185	-	1.0
INA BZ092	IF	BZ092	-	-	-	-	-	2000	3500	200	-	-
	TF	IBZ09	-	178	179.0	4.5	-	2000	2500	185	-	1.0
	IF	BZ507	-	-	-	-	-	2500	3500	220	-	-
INA BZ507	TF	IBZ09	-	359	000.0	4.5	-	2000	2500	185	-	1.0
	IF	IBZ09	-	-	-	-	-	2000	2500	185	-	-
	TF	FBZ09	-	088	089.0	3.5	-	2000	2000	-	-	1.0
APCH	TF	RW09	Yes	088	089.1	5.4	-	-	-	-	-3.00 / 49	0.3
	TF	BZ090	Yes	088	089.2	3.0	-	-	4000	200	-	1.0
	DF	OSGOT	-	-	-	-	L	-	4000	200	-	1.0