

RNP RWY 27												
RMK	MAG VAR 2025 0.9°E										REF NAVID :-	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	BZ277	-	-	-	-	-	-	-	-	-	-
INA BZ277	IF	BZ277	-	-	-	-	-	-	3500	220	-	-
	TF	BZ275	-	358	359.1	4.5	-	2500	3500	220	-	1.0
	TF	BZ276	-	088	089.2	7.0	R	2500	3500	220	-	1.0
	TF	IBZ27	-	189	189.7	4.6	R	2500	2500	200	-	1.0
INA BZ274	IF	BZ274	-	-	-	-	-	2500	5000	-	-	-
	TF	BZ276	-	189	189.8	3.8	-	2500	3500	220	-	1.0
	TF	IBZ27	-	189	189.7	4.6	-	2500	2500	200	-	1.0
INA BIDAC	IF	BIDAC	-	-	-	-	-	2500	5000	-	-	-
	TF	IBZ27	-	299	300.2	6.4	-	2500	2500	200	-	1.0
INA BZ501	IF	BZ501	-	-	-	-	-	2500	3500	220	-	-
	TF	IBZ27	-	359	000.0	4.5	-	2500	2500	200	-	1.0
	IF	IBZ27	-	-	-	-	-	2500	2500	200	-	-
APCH	TF	FBZ27	-	268	269.4	3.8	-	2500	2500	-	-	1.0
	TF	RW27	Yes	268	269.3	7.0	-	-	-	-	-3.00 / 49	0.3
	TF	BZ270	Yes	268	269.1	3.7	-	-	4000	200	-	1.0
	DF	BZ272	-	-	-	-	R	-	4000	200	-	1.0
	TF	BZ274	-	098	099.3	16.3	R	-	4000	220	-	1.0