

BIARRITZ PAYS BASQUE
STAR RNAV RWY 27
(Protégées pour / Protected for CAT A, B, C, D)

| STAR RNAV RWY 27 | | | | | | | | | | | | |
|------------------|--------------------------|-----------------|-------------------------|----------|--------------------|--------------------|---------------|----------------|------------------------------|------------------------------|--------------|--------------------------|
| RMK | GNSS only | | | | MAG VAR 2025 0.9°E | | | | REF NAVAIID : - | | | |
| | Procedure Identification | Path Terminator | Waypoint Identification | Fly Over | Direction MAG (°) | Direction True (°) | Distance (NM) | Turn direction | MNM Altitude (FL or AMSL ft) | MAX Altitude (FL or AMSL ft) | MAX IAS (kt) | Navigation Accuracy (NM) |
| HLDG | | | | | | | | | | | | |
| - | - | BZ277 | - | - | - | - | - | - | - | - | - | - |
| MAGEC 3S | | | | | | | | | | | | |
| - | IF | MAGEC | - | - | - | - | - | - | FL080 | - | - | - |
| - | TF | BZ274 | - | 189 | 190.0 | 8.4 | - | - | 5000* | - | - | 1.0 |
| - | TF | BZ276 | - | 189 | 189.8 | 3.8 | - | 3000 | 3500* | - | - | 1.0 |
| - | TF | IBZ27 | - | 189 | 189.7 | 4.6 | - | 3000 | - | 200 | - | 1.0 |
| - | TF | BZ277 | - | 269 | 269.9 | 6.2 | - | 3000 | - | 200 | - | 1.0 |
| SOVOS 3S | | | | | | | | | | | | |
| - | IF | SOVOS | - | - | - | - | - | - | FL100 | - | - | - |
| - | TF | BIDAC | - | 279 | 280.1 | 10.5 | - | 3000 | 5000* | - | - | 1.0 |
| - | TF | IBZ27 | - | 299 | 300.2 | 6.4 | - | 3000 | - | 200 | - | 1.0 |
| - | TF | BZ277 | - | 269 | 269.9 | 6.2 | - | 3000 | - | 200 | - | 1.0 |
| DONOS 3S | | | | | | | | | | | | |
| - | IF | DONOS | - | - | - | - | - | 6000 | FL090 | - | - | - |
| - | TF | BZ503 | - | 018 | 018.9 | 7.0 | - | 3500 | 6000 | 220 | - | 1.0 |
| - | TF | BZ501 | - | 088 | 089.2 | 7.8 | - | 3000 | 3500* | 220 | - | 1.0 |
| - | TF | IBZ27 | - | 359 | 000.0 | 4.5 | - | 3000 | - | 200 | - | 1.0 |
| - | TF | BZ277 | - | 269 | 269.9 | 6.2 | - | 3000 | - | 200 | - | 1.0 |
| SSN 3S | | | | | | | | | | | | |
| - | IF | SSN | - | - | - | - | - | 6000 | FL090 | - | - | - |
| - | TF | BZ505 | - | 064 | 064.7 | 11.5 | - | 3500 | 6000 | - | - | 1.0 |
| - | TF | BZ503 | - | 088 | 089.1 | 6.7 | - | 3500 | 6000 | 220 | - | 1.0 |
| - | TF | BZ501 | - | 088 | 089.2 | 7.8 | - | 3000 | 3500* | 220 | - | 1.0 |
| - | TF | IBZ27 | - | 359 | 000.0 | 4.5 | - | 3000 | - | 200 | - | 1.0 |
| - | TF | BZ277 | - | 269 | 269.9 | 6.2 | - | 3000 | - | 200 | - | 1.0 |

* Restriction en cas d'arrivée directe autorisée