

INA RNAV RWY 35L												
RMK	Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MAG VAR 2025 (FL or AMSL ft)	2.6 ° E MAX Altitude (FL or AMSL ft)	REF NAVAID : Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
	HLDG	-	ARBON	-	-	-	-	-	-	-	-	-
		-	GOMET	-	-	-	-	-	-	-	-	-
		-	RIPTU	-	-	-	-	-	-	-	-	-
		-	TALAR	-	-	-	-	-	-	-	-	-
		IF	RIPTU						FL070			
	INA RIPTU 3N	TF	LL505		178	180.6	27.9		5000			1.0
		TF	LL503		214	216.7	4.0					1.0
		TF	LL501		214	216.7	4.0		4000	220		1.0
		TF	NEGPU		263	265.5	4.1		3000	4500		1.0
		IF	TALAR						FL070			
	INA TALAR 3N	TF	LL504		151	153.8	24.3					1.0
		TF	LL502		119	121.3	4.0		5000			1.0
		TF	LL500		119	121.3	4.0		4000	220		1.0
		TF	NEGPU		082	085.0	3.9		3000	4500		1.0
		IF	ARBON						FL070			
	INA ARBON 3N	TF	LL514		040	042.5	6.6		5000			1.0
		TF	LL512		040	042.5	4.0					1.0
		TF	LL510		040	042.6	4.0		4000	220		1.0
		TF	NEGPU		351	353.2	4.1		3000	4500		1.0
		IF	GOMET						FL100			
	INA GOMET 3N	TF	LL513		289	291.9	8.6		5000			1.0
		TF	LL511		289	291.7	4.0					1.0
		TF	LL510		289	291.7	4.0		4000	220		1.0
		TF	NEGPU		351	353.2	4.1		3000	4500		1.0