

INA RNAV RWY 35R														
RMK	MAG VAR 2025										26 ° E		REF NAV AID :	
	Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)	
HLDG	-	-	ARBON	-	-	-	-	-	-	-	-	-	-	
	-	-	GOMET	-	-	-	-	-	-	-	-	-	-	
	-	-	RIPTU	-	-	-	-	-	-	-	-	-	-	
	-	-	TALAR	-	-	-	-	-	-	-	-	-	-	
INA RIPTU 3N	IF		RIPTU						FL070					
	TF		LL505		178	180.6	27.9		5000				1.0	
	TF		LL503		214	216.7	4.0						1.0	
	TF		LL501		214	216.7	4.0		4000		220		1.0	
	TF		INGUV		263	265.3	3.9		3000	4500	220		1.0	
INA TALAR 3N	IF		TALAR						FL070					
	TF		LL504		151	153.8	24.3						1.0	
	TF		LL502		119	121.3	4.0		5000				1.0	
	TF		LL500		119	121.3	4.0		4000		220		1.0	
	TF		INGUV		083	085.1	4.1		3000	4500	220		1.0	
INA GOMET 3N	IF		GOMET						FL100					
	TF		LL513		289	291.9	8.6		5000				1.0	
	TF		LL511		289	291.7	4.0						1.0	
	TF		LL510		289	291.7	4.0		4000		220		1.0	
	TF		INGUV		353	355.9	4.0		3000	4500	220		1.0	
INA ARBON 3N	IF		ARBON						FL070					
	TF		LL514		040	042.5	6.6		5000				1.0	
	TF		LL512		040	042.5	4.0						1.0	
	TF		LL510		040	042.6	4.0		4000		220		1.0	
	TF		INGUV		353	355.9	4.0		3000	4500	220		1.0	