

LYON SAINT EXUPERY
SID RNAV RWY 17L
(Protégés pour / Protected for CAT A, B, C, D)

SID RNAV RWY 17L											
RMK	GNSS out/ DME/DME (RU requis/required)	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNVA Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
MABES6S											
-	CF	LL791	YES	173	175.1	-	-	-	-	-	1.0
-	CA	-	-	173	175.1	-	-	1300	-	-	1.0
-	DF	LL795	-	-	-	-	L	-	-	210	1.0
-	TF	DANBO	-	327	329.7	11.7	-	-	-	-	1.0
-	TF	BOBSI	-	350	352.8	24.3	-	FL160	-	-	1.0
-	TF	MABES	-	083	085.1	11.7	R	-	-	-	1.0
RISOR8S											
-	CF	LL793	YES	173	175.1	-	-	-	-	230	1.0
-	CF	PENAR	-	101	104.0	-	-	FL100	-	-	1.0
-	TF	RISOR	-	080	082.3	14.3	-	FL130	-	-	1.0
MOKIP8S											
-	CF	LL791	YES	173	175.1	-	-	-	-	-	1.0
-	CA	-	-	173	175.1	-	-	1300	-	-	1.0
-	DF	LL795	-	-	-	-	L	-	-	210	1.0
-	TF	DANBO	-	327	329.7	11.7	-	-	-	-	1.0
-	TF	BOBSI	-	350	352.8	24.3	-	FL160	-	-	1.0
-	TF	MOKIP	-	028	031.0	8.7	-	FL200	-	-	1.0
ALURA8S											
-	CF	LL791	YES	173	175.1	-	-	-	-	-	1.0
-	CA	-	-	173	175.1	-	-	1300	-	-	1.0
-	DF	LL795	-	-	-	-	L	-	-	210	1.0
-	TF	DANBO	-	327	329.7	11.7	-	-	-	-	1.0
-	TF	BOBSI	-	350	352.8	24.3	-	-	-	-	1.0
-	TF	ALURA	-	350	352.7	10.6	-	-	-	-	1.0
BUSIL6S											
-	CF	LL791	YES	173	175.1	-	-	-	-	-	1.0
-	CA	-	-	173	175.1	-	-	1300	-	-	1.0
-	DF	LL795	-	-	-	-	L	-	-	210	1.0
-	TF	DANBO	-	327	329.7	11.7	-	-	-	-	1.0
-	TF	BUSIL	-	325	327.9	26.4	-	-	-	-	1.0