

LYON SAINT EXUPERY
SID RNAV RWY 35R
(Protégés pour / Protected for CAT A, B, C, D)

SID RNAV RWY 35R											
RMK	GNSS ou/ou DME/DME (IRU requis/required)				MAG VAR 2025 2.6°E				REF NAVAID : LSE		
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
RISOR8N											
-	CF	LL593	YES	353	355.1	-	-	-	-	-	1.0
-	DF	LL597	-	-	-	-	R	-	-	230	1.0
-	TF	LL599	-	122	125.0	9.0	-	-	-	-	1.0
-	TF	PENAR	-	123	125.1	12.9	-	-	-	-	1.0
-	TF	RISOR	-	080	082.3	14.3	-	FL130	-	-	1.0
MOKIP8N											
-	CF	LL593	YES	353	355.1	-	-	-	-	230	1.0
-	TF	LL595	-	351	353.5	6.9	-	-	-	-	1.0
-	TF	BOBSI	-	350	352.2	24.0	-	FL160	-	-	1.0
-	TF	MOKIP	-	028	031.0	8.7	-	FL200	-	-	1.0
ALURA8N											
-	CF	LL593	YES	353	355.1	-	-	-	-	230	1.0
-	TF	LL595	-	351	353.5	6.9	-	-	-	-	1.0
-	TF	BOBSI	-	350	352.2	24.0	-	-	-	-	1.0
-	TF	ALURA	-	350	352.7	10.6	-	-	-	-	1.0
MABES8N											
-	CF	LL593	YES	353	355.1	-	-	-	-	230	1.0
-	TF	LL595	-	351	353.5	6.9	-	-	-	-	1.0
-	TF	BOBSI	-	350	352.2	24.0	-	FL160	-	-	1.0
-	TF	MABES	-	083	085.1	11.7	R	-	-	-	1.0
BUSIL8N											
-	CF	LL593	YES	353	355.1	-	-	-	-	230	1.0
-	TF	LL595	-	351	353.5	6.9	-	-	-	-	1.0
-	TF	BUSIL	-	325	327.1	26.2	-	-	-	-	1.0