

RNP RWY 21												
RMK								MAG VAR 2025 1.7° E			REF NAV AID :-	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MMM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	CTX	-	-	-	-	-	-	-	-	-	-
INA ROXIL	IF	ROXIL	-	-	-	-	-	3000	5000	-	-	-
	TF	ILX21	-	212	213.5	4.6	-	3000	3000	-	-	1.0
	IF	CTX	-	-	-	-	-	3000	3000	220	-	-
INA CTX	TF	LX212	-	303	305.1	4.7	-	3000	3000	220	-	1.0
	TF	LX214	-	033	035.1	7.6	-	3000	3000	185	-	1.0
	TF	ILX21	-	121	122.9	4.5	-	3000	3000	-	-	1.0
INA LX214	IF	LX214	-	-	-	-	-	3000	3000	185	-	-
	TF	ILX21	-	121	122.9	4.5	-	3000	3000	-	-	1.0
	IF	ILX21	-	-	-	-	-	3000	3000	-	-	-
	TF	FLX21	-	212	213.3	4.5	-	3000	3000	-	-	1.0
APCH	TF	RW21	Yes	212	213.3	7.6	-	-	-	-	-3.0° / 44	0.3
	TF	LX210	Yes	212	213.3	5.0	-	-	3000	210	-	1.0
	DF	LX212	-	-	-	-	R	-	3000	210	-	1.0
	TF	LX214	-	033	035.1	7.6	-	3000	3000	185	-	1.0