

LYON BRON
SID RNAV RWY 16
(Protégés pour / Protected for CAT A, B, C)

SID RNAV RWY 16											
RMK	GNSS only						MAG VAR 2020 1.8°E			REF NAVVID : VOR-DME LSE	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
ROMAM 6T											
-	CF	LY690	-	162	163.4	-	-	-	-	-	1.0
-	TF	LY691	-	178	180.0	7.0	-	-	-	-	1.0
-	TF	LY693	-	178	180.0	14.9	-	-	-	-	1.0
-	TF	ROMAM	-	139	140.4	11.5	-	-	-	-	1.0
BELUS 6T											
-	CF	LY690	-	162	163.4	-	-	-	-	-	1.0
-	TF	LY691	-	178	180.0	7.0	-	-	-	-	1.0
-	TF	LY692	-	087	088.7	14.4	L	-	-	-	1.0
-	TF	BELUS	-	045	046.7	15.1	-	-	FL 120	-	1.0
RISOR 6T											
-	CF	LY690	-	162	163.4	-	-	-	-	-	1.0
-	TF	LY691	-	178	180.0	7.0	-	-	-	-	1.0
-	TF	LY692	-	087	088.7	14.4	L	-	-	-	1.0
-	TF	PENAR	-	087	088.9	12.4	-	FL100	-	-	1.0
-	TF	RISOR	-	080	082.3	14.3	-	FL 130	-	-	1.0
BELEP 6T											
-	CF	LY690	-	162	163.4	-	-	-	-	-	1.0
-	TF	LY602	-	183	185.1	3.9	-	-	-	210	1.0
-	TF	LY694	yes	273	275.3	4.2	R	-	-	-	1.0
-	TF	BELEP	-	293	294.3	34.6	-	-	-	-	1.0
REPSI 6T											
-	CF	LY690	-	162	163.4	-	-	-	-	-	1.0
-	TF	LY602	-	183	185.1	3.9	-	-	-	210	1.0
-	TF	LY694	yes	273	275.3	4.2	R	-	-	-	1.0
-	TF	REPSI	-	264	265.7	25.7	-	-	-	-	1.0
MURRO 6T											
-	CF	LY690	-	162	163.4	-	-	-	-	-	1.0
-	TF	LY602	-	183	185.1	3.9	-	-	-	210	1.0
-	TF	MURRO	-	242	243.3	28.8	-	-	-	-	1.0
BUSIL 6T											
-	CF	LY690	-	162	163.4	-	-	-	-	-	1.0
-	TF	LY602	-	183	185.1	3.9	-	-	-	210	1.0
-	TF	LY694	yes	273	275.3	4.2	R	-	-	-	1.0
-	TF	LY695	-	311	313.0	7.3	-	-	-	220	1.0
-	TF	RONIS	-	346	348.0	8.7	-	-	-	-	1.0
-	TF	LY696	-	359	000.7	15.3	-	-	-	-	1.0
-	TF	LY697	-	031	032.7	9.2	-	-	-	-	1.0
-	TF	BUSIL	-	326	328.2	9.1	-	-	-	-	1.0
ALURA 6T											
-	CF	LY690	-	162	163.4	-	-	-	-	-	1.0
-	TF	LY602	-	183	185.1	3.9	-	-	-	210	1.0
-	TF	LY694	yes	273	275.3	4.2	R	-	-	-	1.0
-	TF	LY695	-	311	313.0	7.3	-	-	-	220	1.0
-	TF	RONIS	-	346	348.0	8.7	-	-	-	-	1.0
-	TF	LY696	-	359	000.7	15.3	-	-	-	-	1.0
-	TF	BOBSI	-	031	032.7	20.6	-	-	-	-	1.0
-	TF	ALURA	-	351	352.7	10.6	-	-	-	-	1.0
MOKIP 6T											
-	CF	LY690	-	162	163.4	-	-	-	-	-	1.0
-	TF	LY602	-	183	185.1	3.9	-	-	-	210	1.0
-	TF	LY694	yes	273	275.3	4.2	R	-	-	-	1.0
-	TF	LY695	-	311	313.0	7.3	-	-	-	220	1.0
-	TF	RONIS	-	346	348.0	8.7	-	-	-	-	1.0
-	TF	LY696	-	359	000.7	15.3	-	-	-	-	1.0
-	TF	BOBSI	-	031	032.7	20.6	-	FL160	-	-	1.0
-	TF	MOKIP	-	029	031.0	8.7	-	FL200	-	-	1.0
MABES 6T											
-	CF	LY690	-	162	163.4	-	-	-	-	-	1.0
-	TF	LY602	-	183	185.1	3.9	-	-	-	210	1.0
-	TF	LY694	yes	273	275.3	4.2	R	-	-	-	1.0
-	TF	LY695	-	311	313.0	7.3	-	-	-	220	1.0
-	TF	RONIS	-	346	348.0	8.7	-	-	-	-	1.0
-	TF	LY696	-	359	000.7	15.3	-	-	-	-	1.0
-	TF	BOBSI	-	031	032.7	20.6	-	FL160	-	-	1.0
-	TF	MABES	-	083	085.1	11.7	-	-	-	-	1.0