

**NICE COTE D'AZUR**  
**SID RWY 22 L/R**  
(Protégés pour / Protected for CAT A, B, C, D)

SID RNAV RWY 22L/22R											
RMK	GNSS ou/ or DME/DME/IRU (1) GNSS seulement / only.			MAG VAR 2025 3.0°E						REF NAVAID : AZR	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy
<b>LANKO 8X</b>											
-	CF	22L : MN222 22R : MN221	-	222	225.0	-	-	-	-	-	1.0
-	TF	MN223	-	147	150.0	MN222 : 3.5 MN221 : 3.7	-	-	-	-	1.0
-	TF	MN232	-	129	131.8	7.4	-	6000	-	210	1.0
-	TF	RESBO	-	218	221.1	23.5	-	-	-	-	1.0
-	TF	STP	-	276	279.3	15.9	-	-	-	-	1.0
-	TF	CUERS	-	268	271.3	20.5	-	-	-	-	1.0
-	TF	LANKO	-	268	270.8	5.3	-	-	-	-	1.0
<b>TURIL 8X</b>											
-	CF	22L : MN222 22R : MN221	-	222	225.0	-	-	-	-	-	1.0
-	TF	MN223	-	147	150.0	MN222 : 3.5 MN221 : 3.7	-	-	-	-	1.0
-	TF	MN232	-	129	131.8	7.4	-	6000	-	210	1.0
-	TF	RESBO	-	218	221.1	23.5	-	-	-	-	1.0
-	TF	STP	-	276	279.3	15.9	-	-	-	-	1.0
-	TF	RUBIT	-	268	271.2	8.3	-	-	-	-	1.0
-	TF	TURIL	-	268	271.1	17.0	-	-	-	-	1.0
<b>RUBIT 8X</b>											
-	CF	22L : MN222 22R : MN221	-	222	225.0	-	-	-	-	-	1.0
-	TF	MN223	-	147	150.0	MN222 : 3.5 MN221 : 3.7	-	-	-	-	1.0
-	TF	MN232	-	129	131.8	7.4	-	6000	-	210	1.0
-	TF	RESBO	-	218	221.1	23.5	-	-	-	-	1.0
-	TF	STP	-	276	279.3	15.9	-	-	-	-	1.0
-	TF	RUBIT	-	268	271.2	8.3	-	-	-	-	1.0
<b>EPOLO 8X</b>											
-	CF	22L : MN222 22R : MN221	-	222	225.0	-	-	-	-	-	1.0
-	TF	MN223	-	147	150.0	MN222 : 3.5 MN221 : 3.7	-	-	-	-	1.0
-	TF	MN232	-	129	131.8	7.4	-	6000	-	210	1.0
-	TF	RESBO	-	218	221.1	23.5	-	-	-	-	1.0
-	TF	EPOLO	-	224	226.8	25.7	-	-	-	-	1.0