

CHALONS VATRY
STAR RNAV RWY ALL
(Protégées pour / Protected for CAT A, B, C, D)

STAR RNAV RWY ALL											
RMK	GNSS Only						MAG VAR 2025 2.3°E			REF NAV AID : -	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
HLDG											
OKBUK	-	OKBUK	-	-	-	-	-	-	-	-	-
DIKOL 2P											
	IF	DIKOL	-	-	-	-	-	-	-	250	-
	TF	OK500	-	201	203.4	7.2	-	2700	-	-	1.0
	TF	OKVIG	-	201	203.4	7.4	-	-	-	-	1.0
	TF	OKBUK	-	189	191.0	6.0	-	2500	-	-	1.0
DIKOL 2S											
	IF	DIKOL	-	-	-	-	-	-	-	250	-
	TF	VAXED	-	168	170.0	15.7	-	3500	4000	-	1.0
TRO 2P											
	IF	TRO	-	-	-	-	-	-	-	250	-
	TF	ASRUL	-	348	350.5	28.4	-	-	-	-	1.0
	TF	OKBUK	-	009	011.0	6.0	-	2500	-	-	1.0
TRO 2S											
	IF	TRO	-	-	-	-	-	-	-	250	-
	TF	OK400	-	011	013.0	20.5	-	3500	-	-	1.0
	TF	VAXED	-	003	005.0	17.9	-	3500	4000	-	1.0