

PRECODING INA RNAV (GNSS ou / or DME) RWY 26

INA RNAV RWY 26													
RMK	Leg sequence	MAG VAR 2025 - 2.0° E						REF NAV AID : LEQ					
		Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
	HLDG	-	ASBAR	-	-	-	-	-	-	-	-	-	-
		IF	ASBAR	-	-	-	-	-	3000	-	-	-	-
	INA ASBAR	TF	OSLID	-	010	011.9	6.9	-	2000	4000	220	-	1.0
		TF	OLBUS	-	346	347.7	6.0	-	2000	-	210	-	1.0
	INA OSLID	IF	OSLID	-	-	-	-	-	2000	4000	220	-	-
		TF	OLBUS	-	346	347.7	6.0	-	2000	-	210	-	1.0
	INA UPMIT	IF	UPMIT	-	-	-	-	-	2000	-	170	-	-
		TF	OLBUS	-	166	167.6	3.0	-	2000	-	170	-	1.0
	INA OLBUS	IF	OLBUS	-	-	-	-	-	2000	-	210	-	-