

LILLE LESQUIN
SID RNAV RWY 08
(Protégés pour / Protected for CAT A, B, C, D)

SID RNAV RWY 08											
RMK	(1) FA ou/ou VA acceptable						MAG VAR 2025 2.0°E			REF NAV AID : LEQ	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
ABB 6R											
-	CA (1)	-	-	075	077.0	-	-	557 (400 AAL)	-	-	1.0
-	CF	QQ605	-	210	212.0	6.1	R	-	-	-	1.0
-	TF	OBIVA	-	229	231.4	30.0	-	-	-	-	1.0
-	TF	ABB	-	262	263.6	25.3	-	-	-	-	1.0
BNE 6R											
-	CA (1)	-	-	075	077.0	-	-	557 (400 AAL)	-	-	1.0
-	CF	QQ605	-	210	212.0	6.1	R	-	-	-	1.0
-	TF	IBERU	-	282	283.7	25.8	-	-	-	-	1.0
-	TF	BNE	-	273	274.8	21.1	-	-	-	-	1.0
CIV 6R											
-	CA (1)	-	-	075	077.0	-	-	557 (400 AAL)	-	-	1.0
-	CF	QQ602	-	144	146.0	6.3	R	-	-	-	1.0
-	TF	DENIN	-	132	133.9	10.9	-	-	-	-	1.0
-	TF	CIV	-	049	051.4	19.7	-	-	-	-	1.0
MATIX 6R											
-	CA (1)	-	-	075	077.0	-	-	557 (400 AAL)	-	-	1.0
-	CF	QQ602	-	144	146.0	6.3	R	-	-	-	1.0
-	TF	DENIN	-	132	133.9	10.9	-	-	-	-	1.0
-	TF	MATIX	-	129	131.0	24.8	-	-	-	-	1.0
TRACA 6R											
-	CA (1)	-	-	075	077.0	-	-	557 (400 AAL)	-	-	1.0
-	CF	QQ605	-	210	212.0	6.1	R	-	-	-	1.0
-	TF	IBERU	-	282	283.7	25.8	-	-	-	-	1.0
-	TF	TRACA	-	308	309.6	24.1	-	-	-	-	1.0
VERMA 6R											
-	CA (1)	-	-	075	077.0	-	-	557 (400 AAL)	-	-	1.0
-	CF	QQ602	-	144	146.0	6.3	R	-	-	-	1.0
-	TF	VERMA	-	177	178.7	29.8	-	-	-	-	1.0