

**LILLE LESQUIN**  
**STAR RNAV RWY 08**  
(Protégés pour / Protected for CAT A, B, C, D)

STAR RNAV RWY 08											
RMK	(1) Utilisable uniquement sur instruction ATC / Usable only on ATC requirement						MAG VAR 2025 2.0 °E			REF NAVAID : -	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
<b>HLDG</b>											
ERNOD	-	ERNOD	-	-	-	-	-	-	-	-	-
LEQ	-	LEQ	-	-	-	-	-	-	-	-	-
<b>TRACA 5C</b>											
-	IF	TRACA	-	-	-	-	-	-	-	-	-
-	TF	IBERU	-	127	129.3	24.1	-	-	-	-	1.0
-	TF	ERNOD	-	130	132.4	17.4	-	3000	-	220	1.0
<b>BNE 5C</b>											
-	IF	BNE	-	-	-	-	-	-	-	-	-
-	TF	IBERU	-	092	094.4	21.1	-	-	-	-	1.0
-	TF	ERNOD	-	130	132.4	17.4	-	3000	-	220	1.0
<b>ABB 5C</b>											
-	IF	ABB	-	-	-	-	-	-	-	-	-
-	TF	OBIVA	-	081	083.1	25.3	-	-	-	-	1.0
-	TF	ERNOD	-	038	039.8	17.1	-	3000	-	220	1.0
<b>SULEX 5C</b>											
-	IF	SULEX	-	-	-	-	-	-	-	-	-
-	TF	ERNOD	-	346	347.9	24.7	-	3000	-	220	1.0
<b>CMB 5C</b>											
-	IF	CMB	-	-	-	-	-	-	-	-	-
-	TF	ERNOD	-	305	307.0	17.3	-	3000	-	220	1.0
<b>MATIX 5C</b>											
-	IF	MATIX	-	-	-	-	-	-	-	-	-
-	TF	CMB	-	283	285.1	30.4	-	-	-	-	1.0
-	TF	ERNOD	-	305	307.0	17.3	-	3000	-	220	1.0
<b>CIV 5C</b>											
-	IF	CIV	-	-	-	-	-	-	-	-	-
-	TF	ROBAL	-	230	231.7	9.7	-	-	-	-	1.0
-	TF	DENIN	-	230	231.6	10.0	-	-	-	-	1.0
-	TF	CMB	-	230	231.6	13.7	-	-	-	-	1.0
-	TF	ERNOD	-	305	307.0	17.3	-	3000	-	220	1.0
<b>TRACA 5F (1)</b>											
-	IF	TRACA	-	-	-	-	-	-	-	-	-
-	TF	IBERU	-	127	129.3	24.1	-	-	-	-	1.0
-	TF	EKRIK	-	111	112.7	12.5	-	3000	-	200	1.0
<b>BNE 5F (1)</b>											
-	IF	BNE	-	-	-	-	-	-	-	-	-
-	TF	IBERU	-	092	094.4	21.1	-	-	-	-	1.0
-	TF	EKRIK	-	111	112.7	12.5	-	3000	-	200	1.0
<b>ABB 5F (1)</b>											
-	IF	ABB	-	-	-	-	-	-	-	-	-
-	TF	OBIVA	-	081	083.1	25.3	-	-	-	-	1.0
-	TF	EKRIK	-	024	025.7	22.2	-	3000	-	200	1.0