

**LILLE LESQUIN**  
**STAR RNAV RWY 26**  
(Protégés pour / Protected for CAT A, B, C, D)

STAR RNAV RWY 26											
RMK	(1) Utilisable uniquement sur instruction ATC / Usable only on ATC requirement						MAG VAR 2025 2.0 °E			REF NAVAID : -	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
<b>HLDG</b>											
ASBAR	-	ASBAR	-	-	-	-	-	-	-	-	-
LEQ	-	LEQ	-	-	-	-	-	-	-	-	-
<b>TRACA 5D</b>											
-	IF	TRACA	-	-	-	-	-	-	-	-	-
-	TF	IBERU	-	127	129.3	24.1	-	-	-	-	1.0
-	TF	BARLI	-	127	129.4	15.7	-	-	-	-	1.0
-	TF	CMB	-	128	129.7	19.0	-	-	-	-	1.0
-	TF	ASBAR	-	038	039.5	12.9	-	3000	-	-	1.0
<b>BNE 5D</b>											
-	IF	BNE	-	-	-	-	-	-	-	-	-
-	TF	IBERU	-	092	094.4	21.1	-	-	-	-	1.0
-	TF	BARLI	-	127	129.4	15.7	-	-	-	-	1.0
-	TF	CMB	-	128	129.7	19.0	-	-	-	-	1.0
-	TF	ASBAR	-	038	039.5	12.9	-	3000	-	-	1.0
<b>ABB 5D</b>											
-	IF	ABB	-	-	-	-	-	-	-	-	-
-	TF	OBIVA	-	081	083.1	25.3	-	-	-	-	1.0
-	TF	CMB	-	082	083.6	25.0	-	-	-	-	1.0
-	TF	ASBAR	-	038	039.5	12.9	-	3000	-	-	1.0
<b>CMB 5D</b>											
-	IF	CMB	-	-	-	-	-	-	-	-	-
-	TF	ASBAR	-	038	039.5	12.9	-	3000	-	-	1.0
<b>MATIX 5D</b>											
-	IF	MATIX	-	-	-	-	-	-	-	-	-
-	TF	QQ901	-	310	311.6	8.1	-	-	-	-	1.0
-	TF	ASBAR	-	307	309.5	19.5	-	3000	-	-	1.0
<b>CIV 5D</b>											
-	IF	CIV	-	-	-	-	-	-	-	-	-
-	TF	ROBAL	-	230	231.7	9.7	-	-	-	-	1.0
-	TF	QQ902	-	230	231.8	6.1	-	-	-	-	1.0
-	TF	ASBAR	-	257	259.5	5.6	-	3000	-	-	1.0
<b>MATIX 5F (1)</b>											
-	IF	MATIX	-	-	-	-	-	-	-	-	-
-	TF	QQ901	-	310	311.6	8.1	-	-	-	-	1.0
-	TF	QQ902	-	323	324.6	16.5	-	-	-	-	1.0
-	TF	OSLID	-	322	324.4	7.0	-	2000	4000	220	1.0
<b>CIV 5F (1)</b>											
-	IF	CIV	-	-	-	-	-	-	-	-	-
-	TF	ROBAL	-	230	231.7	9.7	-	-	-	-	1.0
-	TF	QQ902	-	230	231.8	6.1	-	-	-	-	1.0
-	TF	OSLID	-	322	324.4	7.0	-	2000	4000	220	1.0