

LIFOU OUANAHAM

PRECODING RNP RWY 12

RNP RWY 12												
RMK	MAG VAR 2025 12.4° E						REF NAVAID :					
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MINM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	IWL12	-	-	-	-	-	-	-	-	-	-
INA IWL12	IF	IWL12	-	-	-	-	-	1700	-	175	-	-
INA WL600	IF	WL600	-	-	-	-	-	1700	-	175	-	-
	TF	IWL12	-	033	045.0	3.5	-	1700	-	175	-	1.0
INA ONULU	IF	ONULU	-	-	-	-	-	1700	-	180	-	-
	TF	WL600	-	351	003.4	11.3	-	1700	-	175	-	1.0
	TF	IWL12	-	033	045.0	3.5	-	1700	-	175	-	1.0
APCH	IF	IWL12	-	-	-	-	-	1700	-	175	-	-
	TF	FWL12	-	123	135.0	3.5	-	1700	1700	-	-	1.0
	TF	RW12	yes	123	134.9	4.5	-	-	-	-	-3.0 / 50	0.3
	TF	WL610	yes	123	134.9	2.0	-	-	-	-	-	1.0
	DF	WL600	-	-	-	-	R	-	-	175	-	1.0
	TF	IWL12	-	033	045.0	3.5	-	-	1700	175	-	-