

LIFOU OUANAHAM

PRECODING RNP RWY 30

RNP RWY 30													
RMK							MAG VAR 2025 12.4° E			REF NAVAID :			
	Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
	HLDG	-	IWL30	-	-	-	-	-	-	-	-	-	-
	INA IWL30	IF	IWL30	-	-	-	-	-	1700	-	175	-	-
	INA WL700	IF	WL700	-	-	-	-	-	1700	-	175	-	-
		TF	IWL30	-	033	044.9	3.5	-	1700	-	175	-	1.0
		IF	ONULU	-	-	-	-	-	1700	-	180	-	-
	INA ONULU	TF	WL700	-	078	090.4	12.0	-	1700	-	175	-	1.0
		TF	IWL30	-	033	044.9	3.5	-	1700	-	175	-	1.0
		IF	IWL30	-	-	-	-	-	1700	-	175	-	-
		TF	FWL30	-	303	314.9	3.5	-	1700	1700	-	-	1.0
	APCH	TF	RW30	yes	303	314.9	4.0	-	-	-	-	-3.7 / 50	0.3
		TF	WL710	yes	303	314.9	2.0	-	-	-	-	-	1.0
		DF	WL700	-	-	-	-	L	-	-	175	-	1.0
		TF	IWL30	-	033	044.9	3.5	-	-	1700	175	-	1.0