

RAIATEA UTUROA

PRECODING RNP RWY 25

RNP RWY 25												
RMK	MAG VAR 2025 12.8°E						REF NAVAD : -					
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MINM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	RULOM	-	-	-	-	-	-	-	-	-	-
INA RULOM	IF	RULOM	-	-	-	-	-	5000	-	-	-	-
	TF	REDOK	-	029	041.3	8.9	-	3000	-	-	-	1.0
	TF	RIBRA	-	071	083.8	6.0	-	-	-	-	-	1.0
	TF	REVRI	-	161	173.8	6.0	-	2000	-	-	-	1.0
INA REVRI	IF	REVRI	-	-	-	-	-	2000	-	-	-	-
APCH	IF	REVRI	-	-	-	-	-	2000	-	-	-	-
	TF	FTR25	-	251	263.8	6.0	-	2000	2000	-	-	1.0
	TF	MTR25	Yes	251	263.8	3.5	-	-	-	-	-3.00/-	0.3
	TF	TR434	-	251	263.8	6.7	-	-	-	-	-	1.0
	TF	TR435	-	162	175.1	11.5	-	-	-	-	-	1.0
	TF	TR432	-	112	124.9	4.8	-	-	-	-	-	1.0
	TF	TR431	-	042	054.3	10.5	-	-	-	-	-	1.0
	TF	TR436	-	021	033.4	5.8	-	-	-	-	-	1.0
	TF	REVRI	-	341	353.8	5.0	-	2000	-	-	-	1.0