

| FNA RNP RWY20 | | | | | | | | | | | | |
|---|----------------------------------|-------------------------|----------|-------------------|--------------------|---------------|--------------------|------------------------------|------------------------------|---------------|-------------------------------|--------------------------|
| RMK | (*) Radar vectoring before PO420 | | | | | | MAG VAR 2020 1,0°E | | | REF NAVAID :- | | |
| | Path Terminator | Waypoint Identification | Fly Over | Direction MAG (°) | Direction True (°) | Distance (NM) | Turn direction | MNM Altitude (FL or AMSL ft) | MAX Altitude (FL or AMSL ft) | MAX IAS (kt) | Vertical angle (°) / TCH (ft) | Navigation Accuracy (NM) |
| HLDG | - | MOLBA | - | - | - | - | - | - | - | - | - | - |
| INA (AFTER RWY WEST INA RNAV VEBEK OR MOLBA OR ODILO) | TF | PO420 | - | - | - | - | - | 3000 | 3000 | - | - | - |
| | TF | PO421 | - | 254 | 254,7 | 3,0 | - | 3000 | 3000 | - | - | 1,0 |
| | TF | PO422 | - | 292 | 293,0 | 3,0 | - | 3000 | 3000 | - | - | 1,0 |
| | TF | PO423 | - | 292 | 292,9 | 4,0 | - | 2000 | - | - | - | 1,0 |
| | TF | IPO20 | - | 292 | 292,9 | 1,6 | - | 1600 | - | 180 | - | 1,0 |
| | TF | IPO20 | - | - | - | - | - | 1600 | - | 180 | - | - |
| APCH | TF | FPO20 | - | 227 | 228,4 | 3,8 | - | 1600 | 1600 | 180 | - | 1,0 |
| | TF | RW20 | Yes | 197 | 198,4 | 3,5 | - | - | - | - | -3,4° / 49 | 0,3 |
| | TF | PO425 | - | 197 | 198,4 | 13,5 | - | - | - | - | - | 1,0 |
| | TF | MLN | - | 100 | 100,9 | 21,7 | L | - | 4000 | - | - | 1,0 |
| | TF | MOLBA | Yes | 133 | 133,9 | 13,9 | - | FL070 | FL070 | 230 | - | 1,0 |