

PARIS CHARLES DE GAULLE (LFPG)
STAR RNAV Réacteurs et Hélices / Turbofans and Turboprops
RWY 27R

STAR RNAV RWY 27R											
RMK							MAG VAR 2020 1,1°E		REF NAVAID : -		
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
RPL 9P (FIR)											
-	IF	RPL	-	-	-	-	-	-	-	-	-
-	TF	ERTIP	-	291	292.3	36.6	-	-	-	-	1.0
-	TF	NANOP	-	318	318.8	10.2	-	-	-	-	1.0
-	TF	FF301	-	308	309.5	8.1	-	-	FL150	250	1.0
-	TF	URELO	-	308	309.4	18.1	-	-	FL100	-	1.0
-	TF	OKIPA	-	302	303.0	8.0	-	FL070	FL100	-	1.0
DJL 9P (UIR FIR)											
-	IF	DJL	-	-	-	-	-	-	-	-	-
-	TF	FF304	-	321	322.5	25.3	-	-	FL280	-	1.0
-	TF	TRO	-	321	322.2	49.3	-	-	FL150	250	1.0
-	TF	URELO	-	331	331.9	19.6	-	-	FL100	-	1.0
-	TF	OKIPA	-	302	303.0	8.0	-	FL070	FL100	-	1.0
PIBAT 9P (FIR)											
-	IF	PIBAT	-	-	-	-	-	-	-	-	-
-	TF	AVLON	-	337	338.2	48.8	-	-	-	-	1.0
-	TF	TRO	-	007	008.2	41.9	-	-	FL150	250	1.0
-	TF	URELO	-	331	331.9	19.6	-	-	FL100	-	1.0
-	TF	OKIPA	-	302	303.0	8.0	-	FL070	FL100	-	1.0
MOU 9P (FIR)											
-	IF	MOU	-	-	-	-	-	-	-	-	-
-	TF	TRO	-	007	008.2	93.7	-	-	FL150	250	1.0
-	TF	URELO	-	331	331.9	19.6	-	-	FL100	-	1.0
-	TF	OKIPA	-	302	303.0	8.0	-	FL070	FL100	-	1.0
TRO 9P (UIR FIR)											
-	IF	TRO	-	-	-	-	-	-	FL150	250	-
-	TF	URELO	-	331	331.9	19.6	-	-	FL100	-	1.0
-	TF	OKIPA	-	302	303.0	8.0	-	FL070	FL100	-	1.0
KEPER 9W (UIR)											
-	IF	KEPER	-	-	-	-	-	-	FL280	-	-
-	TF	LUMAN	-	034	035.1	9.8	-	-	-	300	1.0
-	TF	ROMGO	-	034	035.1	30.0	-	-	-	300	1.0
-	TF	FF501	-	061	062.4	8.5	-	FL190	FL190	-	1.0
-	TF	NERKI	-	062	062.6	13.2	-	-	FL160	-	1.0
-	TF	BANOX	-	062	062.6	8.0	-	FL140	FL150	300	1.0
KOVAK 9W (FIR)											
-	IF	KOVAK	-	-	-	-	-	-	-	300	-
-	TF	BENAR	-	344	345.3	16.1	-	-	-	-	1.0
-	TF	ROMGO	-	034	035.4	6.9	-	-	-	300	1.0
-	TF	FF501	-	061	062.4	8.5	-	-	-	-	1.0
-	TF	NERKI	-	062	062.6	13.2	-	-	FL160	-	1.0
-	TF	BANOX	-	062	062.6	8.0	-	FL140	FL150	300	1.0
SABLE 9W (FIR)											
-	IF	SABLE	-	-	-	-	-	-	-	-	-
-	TF	LUMAN	-	078	078.8	27.3	-	-	-	300	1.0
-	TF	ROMGO	-	034	035.1	30.0	-	-	-	300	1.0
-	TF	FF501	-	061	062.4	8.5	-	-	-	-	1.0
-	TF	NERKI	-	062	062.6	13.2	-	-	FL160	-	1.0
-	TF	BANOX	-	062	062.6	8.0	-	FL140	FL150	300	1.0