

PRECODING FNA ILS CAT 123 LOC RWY 26R

| FNA ILS CAT I ou/or CAT II et/and CAT III ou/or LOC RWY 26R |                                                                       |                         |          |                   |                    |               |                |                               |                              |              |                              |          |
|-------------------------------------------------------------|-----------------------------------------------------------------------|-------------------------|----------|-------------------|--------------------|---------------|----------------|-------------------------------|------------------------------|--------------|------------------------------|----------|
| RMK                                                         | API / Missed approach : RNAV 1 requis / required                      |                         |          |                   |                    |               |                | MAG VAR 2020 1.1°E            |                              |              | REF NAV AID :-               |          |
| Leg sequence                                                | Path Terminator                                                       | Waypoint Identification | Fly Over | Direction MAG (°) | Direction True (°) | Distance (NM) | Turn direction | MNMM Altitude (FL or AMSL ft) | MAX Altitude (FL or AMSL ft) | MAX IAS (kt) | Vertical angle (°) / TCH (m) | NAV Spec |
| APCH                                                        | IF                                                                    | IG26R                   | -        | -                 | -                  | -             | -              | 4000                          | -                            | -            | -                            | 1.0      |
|                                                             | See chart FNA ILS CAT I ou/or CAT II et/and CAT III ou/or LOC RWY 26R |                         |          |                   |                    |               |                |                               |                              |              |                              |          |
|                                                             | CA                                                                    | -                       | -        | 264               | 265.3              | -             | -              | 2500                          | -                            | -            | -                            | 1.0      |
|                                                             | DF                                                                    | PG442                   | -        | -                 | -                  | -             | -              | -                             | -                            | -            | -                            | 1.0      |
|                                                             | TF                                                                    | AMJUS                   | -        | 339               | 339.8              | 11.5          | -              | 4000                          | 4000                         | -            | -                            | 1.0      |