

PARIS CHARLES DE GAULLE
Réacteurs (R) et hélices (H) / Turbofans (R) and turboprops (H)
SID RNAV RWY 27L - 27R
(Protégés pour / Protected for CAT A, B, C, D)

SID RNAV RWY 27L - 27R											
RMK	MAG VAR 2020 1.1°E										
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	Ref NAVAID : BT MAX IAS (kt)	Navigation Accuracy (NM)
LATRA 7Z											
RWY27L	CF	PG270	-	264	265.3	-	-	-	-	-	1.0
RWY27R			-	261	262.5	-	-	-	-	-	
-	TF	PG290	Y	327	327.9	3.8	-	-	-	-	1.0
-	CF	AMJUS	-	271	272.0	-	-	-	-	-	1.0
-	TF	DEROL	-	170	171.4	25.2	-	-	-	-	1.0
-	TF	LALUX	-	154	154.7	26.1	-	-	-	-	1.0
-	TF	LATRA	-	159	160.4	12.9	-	-	-	280	1.0
OKASI 7Z											
RWY27L	CF	PG270	-	264	265.3	-	-	-	-	-	1.0
RWY27R			-	261	262.5	-	-	-	-	-	
-	TF	PG290	Y	327	327.9	3.8	-	-	-	-	1.0
-	CF	AMJUS	-	271	272.0	-	-	-	-	-	1.0
-	TF	PG289	-	159	160.3	17.7	-	-	-	-	1.0
-	TF	DOPAP	-	156	157.4	7.4	-	-	-	-	1.0
-	TF	ODEBU	-	149	149.9	29.4	-	-	-	-	1.0
-	TF	OKASI	-	152	152.8	13.3	-	-	-	280	1.0
PILUL 7Z											
RWY27L	CF	PG270	-	264	265.3	-	-	-	-	-	1.0
RWY27R			-	261	262.5	-	-	-	-	-	
-	TF	PG290	Y	327	327.9	3.8	-	-	-	-	1.0
-	CF	AMJUS	-	271	272.0	-	-	-	-	-	1.0
-	TF	PG289	-	159	160.3	17.7	-	-	-	-	1.0
-	TF	OXCEL	-	122	123.3	9.7	-	-	-	-	1.0
-	TF	PEKIM	-	146	147.3	32.3	-	-	-	-	1.0
-	TF	PILUL	-	141	142.2	14.6	-	-	-	280	1.0
DORDI 7A											
RWY27L	CF	PG271	-	264	265.3	-	-	-	-	-	1.0
RWY27R			-	261	261.6	-	-	-	-	-	
-	TF	PG272	Y	264	265.2	3.3	-	-	-	-	1.0
-	CF	PG273	-	273	274.0	-	-	-	-	-	1.0
-	TF	PG275	-	190	190.7	9.1	-	-	-	220	1.0
-	TF	OXCEL	-	120	121.2	19.1	-	-	-	-	1.0
-	TF	DORDI	-	151	152.2	34.6	-	-	-	-	1.0
OLZOM 7A											
RWY27L	CF	PG271	-	264	265.3	-	-	-	-	-	1.0
RWY27R			-	261	261.6	-	-	-	-	-	
-	TF	PG272	Y	264	265.2	3.3	-	-	-	-	1.0
-	CF	PG273	-	273	274.0	-	-	-	-	-	1.0
-	TF	PG275	-	190	190.7	9.1	-	-	-	220	1.0
-	TF	OXCEL	-	120	121.2	19.1	-	-	-	-	1.0
-	TF	OLZOM	-	187	188.3	34.9	-	-	-	-	1.0
MONOT 7A											
RWY27L	CF	PG271	-	264	265.3	-	-	-	-	-	1.0
RWY27R			-	261	261.6	-	-	-	-	-	
-	TF	PG272	Y	264	265.2	3.3	-	-	-	-	1.0
-	CF	PG273	-	273	274.0	-	-	-	-	-	1.0
-	TF	PG275	-	190	190.7	9.1	-	-	-	220	1.0
-	TF	OXCEL	-	120	121.2	19.1	-	-	-	-	1.0
-	TF	PG277	-	187	188.3	21.8	-	-	-	-	1.0
-	TF	MONOT	-	160	161.2	18.2	-	-	-	-	1.0
DORDI 7D											
RWY27L	CF	PG271	-	264	265.3	-	-	-	-	-	1.0
RWY27R			-	261	261.6	-	-	-	-	-	
-	TF	PG272	Y	264	265.2	3.3	-	-	-	-	1.0
-	CF	PG273	-	273	274.0	-	-	-	-	-	1.0
-	TF	PG275	-	190	190.7	9.1	-	-	-	220	1.0
-	TF	OXCEL	-	120	121.2	19.1	-	-	-	-	1.0
-	TF	DORDI	-	151	152.2	34.6	-	-	-	-	1.0
OLZOM 7D											
RWY27L	CF	PG271	-	264	265.3	-	-	-	-	-	1.0
RWY27R			-	261	261.6	-	-	-	-	-	
-	TF	PG272	Y	264	265.2	3.3	-	-	-	-	1.0
-	CF	PG273	-	273	274.0	-	-	-	-	-	1.0
-	TF	PG275	-	190	190.7	9.1	-	-	-	220	1.0
-	TF	OXCEL	-	120	121.2	19.1	-	-	-	-	1.0
-	TF	OLZOM	-	187	188.3	34.9	-	-	-	-	1.0