

PARIS CHARLES DE GAULLE
Réacteurs (R) et hélices (H) / Turbofans (R) and turboprops (H)
SID RNAV RWY 27L - 27R
(Protégés pour / Protected for CAT A, B, C, D)

SID RNAV RWY 27L - 27R											
RMK							MAG VAR 2020 1.1°E		Ref NAVAID : BT		
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
MONOT 7D											
RWY27L	CF	PG271	-	264	265.3	-	-	-	-	-	1.0
RWY27R			-	261	261.6	-	-	-	-	-	1.0
-	TF	PG272	Y	264	265.2	3.3	-	-	-	-	1.0
-	CF	PG273	-	273	274.0	-	-	-	-	-	1.0
-	TF	PG275	-	190	190.7	9.1	-	-	-	220	1.0
-	TF	OXCEL	-	120	121.2	19.1	-	-	-	-	1.0
-	TF	MONOT	-	175	176.0	38.9	-	-	-	-	1.0
DORDI 7Z											
RWY27L	CF	PG270	-	264	265.3	-	-	-	-	-	1.0
RWY27R			-	261	262.5	-	-	-	-	-	1.0
-	TF	PG290	Y	327	327.9	3.8	-	-	-	-	1.0
-	CF	AMJUS	-	271	272.0	-	-	-	-	-	1.0
-	TF	PG275	-	190	190.8	12.3	-	-	-	220	1.0
-	TF	OXCEL	-	120	121.2	19.1	-	-	-	-	1.0
-	TF	DORDI	-	151	152.2	34.6	-	-	-	-	1.0
OLZOM 7Z											
RWY27L	CF	PG270	-	264	265.3	-	-	-	-	-	1.0
RWY27R			-	261	262.5	-	-	-	-	-	1.0
-	TF	PG290	Y	327	327.9	3.8	-	-	-	-	1.0
-	CF	AMJUS	-	271	272.0	-	-	-	-	-	1.0
-	TF	PG275	-	190	190.8	12.3	-	-	-	220	1.0
-	TF	OXCEL	-	120	121.2	19.1	-	-	-	-	1.0
-	TF	OLZOM	-	187	188.3	34.9	-	-	-	-	1.0
MONOT 7Z											
RWY27L	CF	PG270	-	264	265.3	-	-	-	-	-	1.0
RWY27R			-	261	262.5	-	-	-	-	-	1.0
-	TF	PG290	Y	327	327.9	3.8	-	-	-	-	1.0
-	CF	AMJUS	-	271	272.0	-	-	-	-	-	1.0
-	TF	PG275	-	190	190.8	12.3	-	-	-	220	1.0
-	TF	OXCEL	-	120	121.2	19.1	-	-	-	-	1.0
-	TF	PG277	-	187	188.3	21.8	-	-	-	-	1.0
-	TF	MONOT	-	160	161.2	18.2	-	-	-	-	1.0
LGL 7A											
RWY27L	CF	PG271	-	264	265.3	-	-	-	-	-	1.0
RWY27R			-	261	261.6	-	-	-	-	-	1.0
-	TF	PG272	Y	264	265.2	3.3	-	-	-	-	1.0
-	CF	PG280	Y	273	274.0	-	-	-	-	-	1.0
-	DF	PG284	-	-	-	-	-	-	-	-	1.0
-	TF	ELCOB	-	262	263.2	16.2	-	-	-	-	1.0
-	TF	LESGA	-	241	242.5	18.6	-	-	-	-	1.0
-	TF	LGL	-	241	241.8	12.4	-	-	-	-	1.0
ELCOB 7A											
RWY27L	CF	PG271	-	264	265.3	-	-	-	-	-	1.0
RWY27R			-	261	261.6	-	-	-	-	-	1.0
-	TF	PG272	Y	264	265.2	3.3	-	-	-	-	1.0
-	CF	PG280	Y	273	274.0	-	-	-	-	-	1.0
-	DF	PG284	-	-	-	-	-	-	-	-	1.0
-	TF	ELCOB	-	262	263.2	16.2	-	-	-	-	1.0
LGL 7D											
RWY27L	CF	PG271	-	264	265.3	-	-	-	-	-	1.0
RWY27R			-	261	261.6	-	-	-	-	-	1.0
-	TF	PG272	Y	264	265.2	3.3	-	-	-	-	1.0
-	CF	PG280	Y	273	274.0	-	-	-	-	-	1.0
-	DF	PG284	-	-	-	-	-	-	-	-	1.0
-	TF	ELCOB	-	262	263.2	16.2	-	-	-	-	1.0
-	TF	LESGA	-	241	242.5	18.6	-	-	-	-	1.0
-	TF	LGL	-	241	241.8	12.4	-	-	-	-	1.0
ELCOB 7D											
RWY27L	CF	PG271	-	264	265.3	-	-	-	-	-	1.0
RWY27R			-	261	261.6	-	-	-	-	-	1.0
-	TF	PG272	Y	264	265.2	3.3	-	-	-	-	1.0
-	CF	PG280	Y	273	274.0	-	-	-	-	-	1.0
-	DF	PG284	-	-	-	-	-	-	-	-	1.0
-	TF	ELCOB	-	262	263.2	16.2	-	-	-	-	1.0
LGL 7Z											
RWY27L	CF	PG270	-	264	265.3	-	-	-	-	-	1.0
RWY27R			-	261	262.5	-	-	-	-	-	1.0
-	TF	PG290	Y	327	327.9	3.8	-	-	-	-	1.0
-	CF	AMJUS	-	271	272.2	-	-	-	-	-	1.0
-	TF	ELCOB	-	262	263.2	32.4	-	-	-	-	1.0
-	TF	LESGA	-	241	242.5	18.6	-	-	-	-	1.0
-	TF	LGL	-	241	241.8	12.4	-	-	-	-	1.0
ELCOB 7Z											
RWY27L	CF	PG270	-	264	265.3	-	-	-	-	-	1.0
RWY27R			-	261	262.5	-	-	-	-	-	1.0
-	TF	PG290	Y	327	327.9	3.8	-	-	-	-	1.0
-	CF	AMJUS	-	271	272.2	-	-	-	-	-	1.0
-	TF	ELCOB	-	262	263.2	32.4	-	-	-	-	1.0