

| RNP RWY 26 | | | | | | | | | | | | |
|--------------|---------------------|-------------------------|----------|-------------------|--------------------|---------------|----------------|------------------------------|------------------------------|--------------|------------------------------|----------|
| RMK | MAG VAR 2020 18,4°W | | | | | | REF NAVAID : | | | | | |
| Leg sequence | Path Terminator | Waypoint Identification | Fly Over | Direction MAG (°) | Direction True (°) | Distance (NM) | Turn direction | MNM Altitude (FL or AMSL ft) | MAX Altitude (FL or AMSL ft) | MAX IAS (kt) | Vertical angle (°) / TCH (m) | NAV Spec |
| HLDG | - | VARUK | - | - | - | - | - | - | - | - | - | - |
| INA LOGUL | IF | LOGUL | - | - | - | - | - | 2000 | - | 220 | - | RNP APCH |
| | TF | VARUK | - | 348 | 329.7 | 5.0 | - | - | - | 220 | - | RNP APCH |
| INA EDNOL | IF | EDNOL | - | - | - | - | - | - | - | 220 | - | RNP APCH |
| | TF | VARUK | - | 168 | 149.6 | 5.0 | - | - | - | 220 | - | RNP APCH |
| APCH | IF | VARUK | - | - | - | - | - | - | - | 220 | - | RNP APCH |
| | TF | FCA26 | - | 258 | 239.7 | 6.5 | - | 2000 | 2000 | - | - | RNP APCH |
| | TF | RW26 | Yes | 264 | 245.3 | 6.0 | - | - | - | - | -3,0 / 15 | RNP APCH |
| | TF | SO510 | - | 264 | 245.3 | 5.7 | - | - | - | - | - | RNP APCH |
| | TF | SO512 | - | 174 | 155.3 | 6.7 | - | - | - | - | - | RNP APCH |
| | TF | LOGUL | - | 077 | 058.1 | 18.9 | L | 2000 | - | - | 220 | - |