

BORDEAUX MERIGNAC

PRECODING RNP A VPT RWY 05

RNP A RWY 05 (VPT)												
RMK	-						MAG VAR 2020 0.3°E			REF NAVAID : -		
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) /TCH (ft)	Navigation Accuracy (NM)
HLDG	-	VAGNA	Yes	225	225.0	4.6	L	5000	FL120	220	-	-
HLDG	-	ETPAR	Yes	165	165.0	4.6	L	5000	FL120	220	-	-
INA VAGNA	IF	VAGNA	-	-	-	-	-	-	-	-	-	-
	TF	BD057	-	277	276.8	10.9	-	-	-	-	-	1.0
	TF	BD05R	-	223	223.5	11.0	-	-	-	220	-	1.0
	TF	BOCEP	-	210	210.2	4.1	-	5000	-	-	-	1.0
	TF	BD05S	-	210	210.2	2.9	-	4000	5000	210	-	1.0
INA ETPAR	TF	FD05A	-	193	193.1	3.2	-	4000	4000	185	-	1.0
	TF	ETPAR	-	-	-	-	-	-	-	220	-	-
	TF	BOCEP	-	173	173.4	16.4	-	5000	-	-	-	1.0
	TF	BD05S	-	210	210.2	2.9	-	4000	5000	210	-	1.0
VISUAL and Missed Approach	TF	FD05A	-	193	193.1	3.2	-	4000	4000	185	-	-
	TF	BD05B	-	193	193.0	1.2	-	-	-	185	-3.40 /49	-
	RF	Center CD051 Radius 2,20NM	BD05C	-	-	5.7	L	-	-	185	-3.40 /49	-
	TF	RW05	Yes	045	045.4	3.6	-	-	-	-	-3.40 /49	-
	TF	BD050	-	045	045.5	3.1	-	-	-	200	-	1.0
	RF	Center CD052 Radius 3,00NM	BD05D	-	-	3.8	L	-	4000	200	-	1.0
	TF	ETPAR	-	333	333.7	19.0	-	-	4000	220	-	1.0
HM	ETPAR	Yes	165	165.0	4.6	L	-	4000	220	-	-	