

TABLEAU POUR LES INTEGRATEURS DE DONNEES

Table for data integrators

RNP RWY 23														
RMK	* basée sur le concept CDO/ based on CDO concept								MAG VAR 2020	0.3°E		REF NAVAID : BMC		
Leg sequence	Path Terminator	Waypoint Identification	DTG THR23 (NM)	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	NAV Spec	
HLDG	-	ETPAR	-	Yes	165	165.0	4.6	L	5000/4000 if API	FL120	220	-	RNAV1	
HLDG	-	VAGNA	-	Yes	225	225.0	4.6	L	5000	FL120	220	-	RNAV1	
HLDG	-	LIBRU	-	Yes	260	260.0	4.6	L	5000	FL120	220	-	RNAV1	
HLDG	-	DIRAX	-	Yes	325	325.0	4.2	L	5000	FL090	220	-	RNAV1	
INA ETPAR*	IF	ETPAR	33,1	-	-	-	-	-	-	-	-	-	RNAV1	
	TF	BD231	21,1	-	122	122.8	12.0	-	-	-	220	-	RNAV1	
	TF	IBD23	12.8	-	135	135.5	8.3	R	3000	4000	210	-	RNAV1	
INA VAGNA*	IF	VAGNA	21.8	-	-	-	-	-	-	-	-	-	RNAV1	
	TF	IBD23	12.8	-	224	224.7	9.1	-	3000	4000	210	-	RNAV1	
INA LIBRU*	IF	LIBRU	27.8	-	-	-	-	-	-	-	-	-	RNAV1	
	TF	BD232	20.6	-	272	272.6	7.2	-	-	-	220	-	RNAV1	
	TF	IBD23	12.8	-	315	315.6	7.8	L	3000	4000	210	-	RNAV1	
INA DIRAX*	IF	DIRAX	41,6	-	-	-	-	-	-	-	-	-	RNAV1	
	TF	BD232	20.6	-	011	11.2	21.0	-	-	-	220	-	RNAV1	
	TF	IBD23	12.8	-	315	315.6	7.8	L	3000	4000	210	-	RNAV1	
APCH	IF	IBD23	12.8	-	-	-	-	-	3000	4000	210	-	RNP APCH	
	TF	FBD23	8.8	-	225	225.6	4.0	-	3000	3000	-	-	RNP APCH	
	TF	RW23	-	Yes	225	225.6	8.8	-	-	-	-	-3.0°/ 16,5	RNP APCH	
	TF	BD230	-	Yes	225	225.5	4.1	-	-	4000	210	-	RNP APCH	
	DF	ETPAR	-	-	-	-	-	R	-	-	220	-	RNP APCH	