

TABLEAU POUR LES INTEGRATEURS DE DONNEES

Table for data integrators

RNP RWY 29													
RMK	* basée sur le concept CDO/ based on CDO concept								MAG VAR 2020 0.3°E			REF NAV AID : BMC	
Leg sequence	Path Terminator	Waypoint Identification	DTG THR29 (NM)	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	NAV Spec
HLDG	-	ETPAR	-	Yes	165	165.0	4.6	L	5000/4000 if API	FL120	220	-	RNAV1
HLDG	-	VAGNA	-	Yes	225	225.0	4.6	L	5000	FL120	220	-	RNAV1
HLDG	-	LIBRU	-	Yes	260	260.0	4.6	L	5000	FL120	220	-	RNAV1
HLDG	-	DIRAX	-	Yes	325	325.0	4.2	L	5000	FL090	220	-	RNAV1
INA ETPAR*	IF	ETPAR	47,5	-	-	-	-	-	-	-	220	-	RNAV1
	TF	BD291	18.2	-	134	134.5	29.3	-	-	6000	220	-	RNAV1
	TF	IBD29	13.0	-	196	196.7	5.5	R	3000	4000	200	-	RNAV1
INA VAGNA*	IF	VAGNA	32.9	-	-	-	-	-	-	-	220	-	RNAV1
	TF	BD291	18.2	-	185	185.8	14.7	-	-	6000	220	-	RNAV1
	TF	IBD29	13.0	-	196	196.7	5.5	R	3000	4000	200	-	RNAV1
INA LIBRU*	IF	LIBRU	24.8	-	-	-	-	-	-	-	220	-	RNAV1
	TF	IBD29	13.0	-	231	231.2	12.0	-	3000	4000	200	-	RNAV1
INA DIRAX*	IF	DIRAX	25.6	-	-	-	-	-	-	-	220	-	RNAV1
	TF	BD292	18.7	-	008	008.7	6.9	-	3000/5000(1)	6000	220	-	RNAV1
	TF	IBD29	13.0	-	008	008.7	6.0	-	3000	4000	200	-	RNAV1
APCH	IF	IBD29	13.0	-	-	-	-	-	3000	4000	200	-	RNP APCH
	TF	FBD29	8.8	-	286	286.6	4.2	-	3000	3000	-	-	RNP APCH
	TF	RW29	-	Yes	286	286.6	8.8	-	-	-	-	-3°/ 15.2	RNP APCH
	TF	BD290	-	Yes	286	286.4	2.0	-	-	-	185	-	RNP APCH
	TF	ETPAR	-	-	347	347.2	22.2	-	4000	-	220	-	RNP APCH

(1) 5000 MNM only if activity in R204 L3.